

T9 Circline Plus

FC40/840

0001967

Product features



PRODUCT OVERVIEW

Product name	FC40/840
Technology	Fluorescent
Watt (Rated) (W)	40
Lamp shape	Ring
Type	T9 Circline Plus
Cap/Base	G10q
Lamp finish	Frosted/Coated
Fixture rating	Enclosed
General application	Education, Hospitality, Logistics & Industry, Museums & Galleries, Office, Retail, Residential & Consumer
ETIM Class	EC000108
E-number FI	4940729
E-number Norway	3845367
Luminous flux (lm)	2900
Colour temperature (K)	4000
Light colour	Cool White
Colour Code	840
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM5
Photobiological Risk Group	Not applicable
Wattage (W)	40
Product Voltage (V)	115
Dimmable	Yes
Dimming method	Mains: leading / trailing edge
Average life (Nominal) (h)	12000
Product EAN number	5410288019673

DATA TABLE

General data

Product name	FC40/840
Technology	Fluorescent
Watt (Rated) (W)	40
Lamp shape	Ring

T9 Circline Plus

FC40/840

0001967

Type	T9 Circline Plus
Cap/Base	G10q
Lamp finish	Frosted/Coated
Fixture rating	Enclosed
General application	Education, Hospitality, Logistics & Industry, Museums & Galleries, Office, Retail, Residential & Consumer
ETIM Class	EC000108
E-number FI	4940729
E-number Norway	3845367

Optical data

Luminous flux (lm)	2900
Luminous flux (Rated) (lm)	2900
Ambient temperature for maximum luminous flux (°C)	25
Colour temperature (K)	4000
Light colour	Cool White
Colour Code	840
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM5
Adjustable chromaticity	N
Photobiological Risk Group	Not applicable
Rated lumen maint. factor (%) at 4000 h 50Hz	78
Rated lumen maint. factor (%) at 6000 h 50Hz	77
Rated lumen maint. factor (%) at 8000 h 50Hz	76
Rated lumen maint. factor (%) at 12000 h 50Hz	74

Electrical data

Wattage (W)	40
Current (A)	0.415
Product Voltage (V)	115
Control gear required	Yes
Transformer required	No
Dimmable	Yes
Dimming method	Mains: leading / trailing edge
Lamp Energy Label (class)	G
kWh per 1000 hours burning time	44

Lifetime data

Average life (Nominal) (h)	12000
Average life (Rated) (h)	12000
Rated survival factor (%) at 2000 h 50Hz	99
Rated survival factor (%) at 4000 h 50Hz	97
Rated survival factor (%) at 6000 h 50Hz	92
Rated survival factor (%) at 8000 h 50Hz	85
Rated survival factor (%) at 12000 h 50Hz	50

T9 Circline Plus

FC40/840
0001967

Physical data

Nominal Product Height (mm)	29
Nominal Product Diameter (mm)	400
Max. Length base to base (mm) - A	400
Length base to pin Min-Max (mm) - B	400
Max. Lamp Diameter (mm) - D	29
Weight (kg)	0.234


Packaging

Single packaging type	Carton
Product EAN number	5410288019673
Packaging single length / height (cm)	40.7
Packaging single width (cm)	3.6
Packaging single depth (cm)	40.8
DUN14 (outer)	15410288019670
Units per outer package	12
Packaging outer length / height (cm)	42.3
Packaging outer width (cm)	41.8
Packaging outer depth (cm)	43.1


Safety data

Lamp mercury content (mg)	3.5
Breakage cleaning instructions	Applicable
Special purpose lamp	No
Suitable for household illumination	Yes


PHOTOMETRY



TECHNICAL DRAWINGS



T9 Circline Plus
FC40/840
0001967




40
kWh/1000h



T9 Circline Plus
FC40/840
0001967



0001967



40
kWh/1000h

