

T8 Coloured

F18W/T8/P

0002560



Range Features

- High quality fluorescent tubes
- Long life
- Available in five colours: Blue, Green, Red, Pink and Yellow
- Applications
- To create special lighting effects in shop windows, bars, fairground attractions, dance halls and discotheques



PRODUCT OVERVIEW

Lamp finish	Coated
Lamp shape	Tubular
Dimmable	Yes
EAN code	5410288025605
Cap/Base	G13
Туре	T8 Coloured
Watt (Nominal) (W)	18
Ordering number	0002560
Luminous flux (Rated) (lm)	550
Technology	Fluorescent
Voltage (V)	57

DATA TABLE

Ger	neral	data

Average life (Nominal) (h)	8000
Control gear required	Yes
Lamp finish	Coated
Lamp shape	Tubular
Dimmable	Yes
EAN code	5410288025605
Fixture rating	Open
General application	Retail; Hospitality; Logistics and Industry; Museums; Education; Office: Residential & Consumer



T8 Coloured

F18W/T8/P

0002560

IEC Reference	IEC 60081
IEC Reference 2	IEC 61195
Intended purpose	Special lighting
Cap/Base	G13
Туре	T8 Coloured
Ordering number	0002560
Range features	High quality fluorescent tubes Long life Available in five colours: Blue, Green, Red, Pink and Yellow Applications To create special lighting effects in shop windows, bars, fairground attractions, dance halls and discotheques
Product name	F18W/T8/P
Special purpose lamp	Yes
Technology	Fluorescent
Transformer required	No
Sales pack quantity	25
E-number SE	8356729
E-number FI	4942912
Electrical data	15 1.20 1.2
	0.37
Electrical data	
Electrical data Current (A)	0.37
Electrical data Current (A) Watt (Nominal) (W)	0.37 18
Electrical data Current (A) Watt (Nominal) (W) Watt (Rated) (W)	0.37 18 18
Electrical data Current (A) Watt (Nominal) (W) Watt (Rated) (W) Voltage (V)	0.37 18 18
Current (A) Watt (Nominal) (W) Watt (Rated) (W) Voltage (V) Physical data	0.37 18 18 57
Electrical data Current (A) Watt (Nominal) (W) Watt (Rated) (W) Voltage (V) Physical data Max. Lamp Diameter (mm) - D	0.37 18 18 57
Electrical data Current (A) Watt (Nominal) (W) Watt (Rated) (W) Voltage (V) Physical data Max. Lamp Diameter (mm) - D Lamp Length (mm) - C/L	0.37 18 18 57
Electrical data Current (A) Watt (Nominal) (W) Watt (Rated) (W) Voltage (V) Physical data Max. Lamp Diameter (mm) - D Lamp Length (mm) - C/L Length base to base (mm) - A	0.37 18 18 57 26 604 589.8
Electrical data Current (A) Watt (Nominal) (W) Watt (Rated) (W) Voltage (V) Physical data Max. Lamp Diameter (mm) - D Lamp Length (mm) - C/L Length base to base (mm) - A Length base to pin Min-Max - B	0.37 18 18 57 26 604 589.8 594.5-596.9
Electrical data Current (A) Watt (Nominal) (W) Watt (Rated) (W) Voltage (V) Physical data Max. Lamp Diameter (mm) - D Lamp Length (mm) - C/L Length base to base (mm) - A Length base to pin Min-Max - B Single packaging type	0.37 18 18 18 57 26 604 589.8 594.5-596.9 Box/Sleeve
Electrical data Current (A) Watt (Nominal) (W) Watt (Rated) (W) Voltage (V) Physical data Max. Lamp Diameter (mm) - D Lamp Length (mm) - C/L Length base to base (mm) - A Length base to pin Min-Max - B Single packaging type Weight (kg)	0.37 18 18 18 57 26 604 589.8 594.5-596.9 Box/Sleeve

TECHNICAL DRAWINGS



T8 Coloured *F18W/T8/P*

0002560

