

T8 Coloured

F18W/T8/G

0002562



Range Features

- Range of T8 fluorescent lamps with a coloured phosphor coating
- Available in red, yellow, green and blue colours
- Used to create special lighting effects in shop windows, bars, fairground attractions, dance halls and discothegues



PRODUCT OVERVIEW

Lamp finish	Coated
Lamp shape	Tubular
Dimmable	Yes
EAN code	5410288025629
Cap/Base	G13
Туре	T8 Coloured
Watt (Nominal) (W)	18
Ordering number	0002562
Luminous flux (Rated) (lm)	1300
Technology	Fluorescent
Voltage (V)	57

DATA TABLE

General	data
GCHCIGI	autu

Average life (Nominal) (h)	8000
Control gear required	Yes
Lamp finish	Coated
Lamp shape	Tubular
Dimmable	Yes
EAN code	5410288025629
Fixture rating	Open
General application	Retail; Hospitality; Logistics and Industry; Museums; Education; Office; Residential & Consumer



T8 Coloured

F18W/T8/G

0002562

IEC Reference	IEC 60081
IEC Reference 2	IEC 61195
Intended purpose	Special lighting
Cap/Base	G13
Туре	T8 Coloured
Ordering number	0002562
Range features	Range of T8 fluorescent lamps with a coloured phosphor coating Available in red, yellow, green and blue colours Used to create special lighting effects in shop windows, bars, fairground attractions, dance halls and discotheques
Product name	F18W/T8/G
Special purpose lamp	Yes
Technology	Fluorescent
Transformer required	No
Sales pack quantity	25
E-number SE	8356731
E-number FI	4942916
Electrical data	
Electrical data Current (A)	0.37
Current (A) Watt (Nominal) (W)	0.37 18
Current (A)	
Current (A) Watt (Nominal) (W)	18
Current (A) Watt (Nominal) (W) Watt (Rated) (W)	18 18
Current (A) Watt (Nominal) (W) Watt (Rated) (W) Voltage (V) Physical data	18 18
Current (A) Watt (Nominal) (W) Watt (Rated) (W) Voltage (V)	18 18 57
Current (A) Watt (Nominal) (W) Watt (Rated) (W) Voltage (V) Physical data Max. Lamp Diameter (mm) - D	18 18 57
Current (A) Watt (Nominal) (W) Watt (Rated) (W) Voltage (V) Physical data Max. Lamp Diameter (mm) - D Lamp Length (mm) - C/L	18 18 57 26 604
Current (A) Watt (Nominal) (W) Watt (Rated) (W) Voltage (V) Physical data Max. Lamp Diameter (mm) - D Lamp Length (mm) - C/L Length base to base (mm) - A	18 18 57 26 604 589.8
Current (A) Watt (Nominal) (W) Watt (Rated) (W) Voltage (V) Physical data Max. Lamp Diameter (mm) - D Lamp Length (mm) - C/L Length base to base (mm) - A Length base to pin Min-Max - B	18 18 57 26 604 589.8 594.5-596.9
Current (A) Watt (Nominal) (W) Watt (Rated) (W) Voltage (V) Physical data Max. Lamp Diameter (mm) - D Lamp Length (mm) - C/L Length base to base (mm) - A Length base to pin Min-Max - B Single packaging type Weight (kg)	18 18 57 26 604 589.8 594.5-596.9 Box/Sleeve
Current (A) Watt (Nominal) (W) Watt (Rated) (W) Voltage (V) Physical data Max. Lamp Diameter (mm) - D Lamp Length (mm) - C/L Length base to base (mm) - A Length base to pin Min-Max - B Single packaging type	18 18 57 26 604 589.8 594.5-596.9 Box/Sleeve

TECHNICAL DRAWINGS

