

Blacklight BL368 Compact MiniLynx


MiniLynx 20W BL368

0025706



Range Features

- Features
- These BL368 tubes emit an upgraded highly concentrated radiation with peak around 368nm. Flying insect - eye sensitivity is generally at or near this frequency
- 100% improvement in effectiveness (at 368nm)
- Depreciation of UV-A output over time is significantly reduced (80% at 5000hrs of original 100 hour output)
- Performs longer and better throughout the insect season
-
- Directions for use
- Maximum exposure limits are set by EN60335 2-59:1997 at an effective 1,0 milliWatt per metre squared (1,0 mW/m) measured at a distance of 1 metre - originally based on the recommendations of the National Radiological Protection Board in the UK. The irradiance value for a single BL BL368-lamp measured without reflector and/or fixture, in free air at 25 celsius, is varying between 0,2 and 0,4 mW/m depending on the wattage



PRODUCT OVERVIEW

Farbtemperatur (K)	UV-A lamp
EAN-Code	5410288257068
Verschluss/Sockel	E27
Typ	BL368
Watt (Nennleistung) (W)	20
Bestellnummer	0025706
Technologie	Fluorescent
Spannung (V)	230

DATENTABELLE

Optische Daten

Farbtemperatur (K)	UV-A lamp
--------------------	-----------

Allgemeine Daten

EAN-Code	5410288257068
Allgemeiner Einsatz	Retail; Hospitality; Logistics and Industry; Museums; Education; Office; Residential & Consumer
Einsatzzweck	Special lighting
Verschluss/Sockel	E27
Typ	BL368
Bestellnummer	0025706

Blacklight BL368 Compact MiniLynx

MiniLynx 20W BL368

0025706

Lange Bezeichnung	Features These BL368 tubes emit an upgraded highly concentrated radiation with peak around 368nm. Flying insect - eye sensitivity is generally at or near this frequency 100% improvement in effectiveness (at 368nm) Depreciation of UV-A output over time is significantly reduced (80% at 5000hrs of original 100 hour output) Performs longer and better throughout the insect season
	Directions for use Maximum exposure limits are set by EN60335 2-59:1997 at an effective 1,0 milliWatt per metre squared (1,0 mW/m) measured at a distance of 1 metre - originally based on the recommendations of the National Radiological Protection Board in the UK. The irradiance value for a single BL BL368-lamp measured without reflector and/or fixture, in free air at 25 celsius, is varying between 0,2 and 0,4 mW/m depending on the wattage
Produktname	MiniLynx 20W BL368
Lampen für spezielle Einsatzbereiche	Yes
Technologie	Fluorescent
Menge/Verpackungseinheit	10
E-Nummer FI	4940706

Elektrische Daten

Watt (Nennleistung) (W)	20
Spannung (V)	230

Physikalische Daten

Verpackungsbezeichnung	Box/Sleeve
Gewicht (kg)	0.09

TECHNISCHE ZEICHNUNGEN

E27

