



# Halogen Low Voltage

## ELC/10H 250W GX5.3 24V 1CT/24

The long lifetime of most of the Halogen Low Voltage lamps is further extended by the unique P3 technology developed by Philips. This allows the lamp to be used at higher temperatures, thereby extending the lamp's lifetime, reducing early failures, and resulting in fewer maintenance man hour costs. P3 also ensures consistency of high-quality light output, and allows the lamp to be used in any burning position, which enables more compact fixture designs. In addition, the compact filament produces a clean white light and high beam intensity for true natural colors on stage and without any hotspots.


### Product data

<b>General Information</b>	
Cap-Base	GX5.3 [GX5.3]
Operating Position	UNIVERSAL [Any or Universal (U)]
Life to 50% Failures (Nom)	1,000 hour(s)
<b>Light Technical</b>	
Color rendering index (CRI)	100
<b>Operating and Electrical</b>	
Power Consumption	250 W
Voltage (Nom)	24 V
Voltage (Nom)	24 V
<b>Controls and Dimming</b>	
Dimmable	Yes
<b>Mechanical and Housing</b>	
Bulb Material	Quartz-UV Open

Reflector Finish	Smooth
Bulb Shape	R50 [R 50mm]
<b>Product Data</b>	
Full product code	871150043686330
Order product name	ELC/10H 250W GX5.3 24V 1CT/24
Order code	924913220540
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	24
Material Nr. (12NC)	924913220540
Full product name	ELC/10H 250W GX5.3 24V 1CT/24
EAN/UPC - Case	8711500436870
EAN/UPC - Product/Case	8711500436863

# Halogen Low Voltage

## Dimensional drawing



Product	D (max)	C (max)
ELC/10H 250W GX5.3 24V 1CT/24	50 mm	44.5 mm

