



Halogen reflector

13164 200W GX5.3 24V 1CT/24

Philips' halogen reflector lamps offer the ideal no-fuss solution for a wide variety of medical, projection and scientific illumination systems. Their proven reliability makes them ideal for retrofit installations. The burners are precisely aligned for optimal light performance. Dichroic reflectors ensure heat dissipation towards the back of the optical system, which helps the optical system remain within temperature limits. A special blue-filter version blocking out unwanted light above 700 nm is available for dental curing applications. In addition, you get all the proven advantages of halogen technology such as a CRI of 100 – the same as natural sunlight for the best possible color rendering. Halogen lamps also create a comfortable warm white light, and they maintain their high lumen output with almost no lumen reduction throughout their lifetime.


Product data

| General Information | |
|-----------------------------|--|
| Cap-Base | GX5.3 [GX5.3] |
| Operating Position | S90 [Standing +/-90D or Base Down (BDH)] |
| Life to 50% Failures (Nom) | 50 hour(s) |
| Light Technical | |
| Color rendering index (CRI) | 100 |
| Operating and Electrical | |
| Power Consumption | 200 W |
| Voltage (Nom) | 24 V |
| Voltage (Nom) | 24 V |
| Controls and Dimming | |
| Dimmable | Yes |

| Mechanical and Housing | |
|---------------------------------|-----------------------------|
| Bulb Material | Quartz-UV Open |
| Reflector Finish | Smooth |
| Product Data | |
| Full product code | 871150041058030 |
| Order product name | 13164 200W GX5.3 24V 1CT/24 |
| Order code | 923921120594 |
| Numerator - Quantity Per Pack | 1 |
| Numerator - Packs per outer box | 24 |
| Material Nr. (12NC) | 923921120594 |
| Full product name | 13164 200W GX5.3 24V 1CT/24 |
| EAN/UPC - Case | 8711500419026 |
| EAN/UPC - Product/Case | 8711500410580 |

Halogen reflector

Dimensional drawing



| Product | D (max) | C (max) |
|-----------------------------|---------|---------|
| 13164 200W GX5.3 24V 1CT/24 | 50.7 mm | 44.5 mm |

