



MASTERColour CDM-T Elite MW

CDM-TP MW 210W/930 PGZX18.1CT/12

The medium wattage lighting system that gives superior, longer-lasting white light for both indoor and outdoor use

Product data

• General Information

Cap-Base	PGZX18. [PGZX18.]
Bulb Shape	T12 [38 mm (T12)]
Operating Position	UNIVERSAL [Any or Universal (U)]
Life To 5% Failures (Nom)	10000 h
Life To 10% Failures (Nom)	12000 h
Life To 50% Failures (Nom)	30000 h
ANSI Code HID	C183/O
Features	Protected (P)

• Light Technical

Color Code	930 [CCT of 3000K]
Luminous Flux (Rated) (Min)	21200 lm
Luminous Flux (Rated) (Nom)	23300 lm
Color Designation	Warm White (WW)
Lumen Maintenance 12000 h (Nom)	78 %
Lumen Maintenance 10000 h (Nom)	84 %
Lumen Maintenance 2000 h (Nom)	98 %
Lumen Maintenance - 40% Life	88 %
Lumen Maintenance 5000 h (Nom)	91 %
Lumen Maintenance - 10% Life	98 %
Saturated Red	50
Design Mean Lumens	21600 lm
Chromaticity Coordinate X (Nom)	0.438

Chromaticity Coordinate Y (Nom)	0.399
Correlated Color Temperature (Max)	- K
Correlated Color Temperature (Min)	- K
Correlated Color Temperature (Nom)	2940 K
Luminous Efficacy (rated) (Min)	101 lm/W
Luminous Efficacy (rated) (Nom)	111 lm/W
Color Rendering Index (Min)	87
Color Rendering Index (Nom)	90

• Operating and Electrical

Power (Rated) (Nom)	210.0 W
Lamp Current Run-Up (Nom)	3.2 A
Ignition Supply Voltage (Max)	4000 V
Ignition Peak Voltage (Max)	4000 V
Ignition Supply Voltage (Min)	3000 V
Re-Ignition Time (Min) (Max)	10 min
Ignition Time (Max)	3 s
Voltage (Max)	115 V
Voltage (Min)	90 V
Voltage (Nom)	100 V

PHILIPS

• Controls and Dimming

Run-Up Time 90% (Max)	1.5 min
-----------------------	---------

• Mechanical and Housing

Bulb Finish	Clear
Overall Length (Max)	7.6 in

• Approval and Application

Energy Efficiency Label (EEL)	A+
Picogram Per Lumen Hour	53 pg/lm.h
Mercury (Hg) Content (Max)	24.5 mg
Energy Consumption kWh/1000 h	231 kWh

• UV

Pet (Niosh) (Nom)	23 h/500lx
Damage Factor D/fc (Nom)	0.13

• Luminaire Design Requirements

Bulb Temperature (Max)	350 °C
Cap-Base Temperature (Nom)	250 °C
Pinch Temperature (Max)	300 °C

• Product Data


Full product code	871829113954600
Order product name	CDM-TP MW 210W/930 PGZX18.1CT/12
EAN/UPC - Product	8727900862096
Order code	928601167031
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	12
Material Nr. (12NC)	928601167031
Net Weight (Piece)	200.000 g
ILCOS Code	MTS-210/30/1A-H-PGZX18

Warnings and Safety

- Use only in totally enclosed luminaire, even during testing, except for protected versions with PGZX18 cap, which are designed for open luminaires (IEC61167, IEC 62035, IEC60598)
- The luminaire must be able to contain hot lamp parts if the lamp ruptures
- Use only with electronic control gear

- Control gear must include end-of-life protection (IEC61167, IEC 62035)
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Dimensional drawing





PGZX18/PGZX18., T12/TMW28


CDM TMW 210W/930 PGZX18. U P

Product	D	D	C
CDM-TP MW 210W/930 PGZX18.1CT/12	193 mm		

Dimensional drawing



Photometric data



© 2016 Philips Lighting Holding B.V.
All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. (Royal Philips) or their respective owners.

www.philips.com/lighting

2016, October 11
data subject to change