



Discharge - Single Ended Hot Restrike csr125/se/HR 48461

Product information

Compact, single ended metal halide hot restrike lamps for a variety of applications requiring high luminance, reliability and excellent colour characteristics. Excellent colour rendering, Ra>90, and high CCT 5600–6000 K with superior colour stability- Universal burn position with hot restrike capability- High efficiency with excellent lumen maintenance -Available with UV blocking.


Application areas



Film and Broadcast













Product data

Cap/Base	GZX9.5
Bulb Shape	Tubular
Bulb Finish	Clear
Bulb Diameter [mm]	15.9
Maximum Overall Length [mm]	75
Light Center Length [mm]	39
Arc Gap	4
Net weight per piece [g]	170
Gross weight per piece [g]	180
Operating position	U - Universal
Brand	General Electric (GE)

Performance data

Colour Code	954
Colour Rendering Index (CRI) [Ra]	90
Nominal correlated colour temperature (CCT) [K]	5400
Nominal lumens [lm]	9800
Energy efficiency class (EEC)	А
Nominal chromaticity coordinate X	0.337
Nominal chromaticity coordinate Y	0.329
Weighted energy consumption [kWh/1000h]	137.5

Electrical data

Nominal power [W]	125
Nominal lamp voltage [V]	80
Lamp Current [A]	1.6
Dimming Capability	No
Ballast Required	Yes





Logistic data

20043168484613
0043168484619
10
BOX
OUTER BOX
480 EUR, 600 UK
480
600
5280
5400
195 × 84 × 100 (mm)
Available

Downloads & Links Go to the catalog site (HTTP) Entertainment Solution Spectrum Catalogue (PDF) Lighting design tools & calculators (HTTP) High-res images / Technical drawings (HTTP) Certificate for the Quality Management System of GE Lighting EMEA (PDF) Certificate for the Environmental Management System of GE Lighting EMEA (PDF)

Disclaimer

Special Purpose Lamp, Not suited for household illumination