

DECOSTAR 51 PRO 50 W 12 V 24° GU5.3

DECOSTAR 51 PRO | Halogen dichroic reflector lamps with 51 mm diameter



Areas of application

- General illumination
- Kitchen lighting
- Dining table lighting
- Mirror lighting
- Workplace lighting
- Shops
- Restaurants, hotels and similar prestigious applications

Product benefits

- Brilliant accent lighting
- Significantly lower CO₂ emissions compared to standard version
- Constant luminous intensity and constant color location throughout the lifetime
- Approved for use in open luminaires (to IEC 60598-1)
- UV filter
- Contains no mercury

Product features

- Average life: 5,000 h
- 100 % dimmable
- Color rendering index R₂: 100
- Color temperature: 3,000 K
- Diameter: 51 mm
- Deco cover
- IRC technology

Technical data

Electrical data

| Nominal wattage | 50.00 W |
|--|---------|
| Nominal voltage | 12.0 V |
| Rated wattage | 50.00 W |
| Number of switching cycles | 125000 |
| Power factor λ | 1.00 |
| Claimed equiv. conventional lamp power | 75 W |


Photometrical data

| Nominal useful luminous flux 90° | 870 lm |
|----------------------------------|------------|
| Luminous intensity | 5300 cd |
| Color temperature | 3000 K |
| Light color (designation) | Warm White |
| Color rendering index Ra | 100 |
| Rated useful luminous flux 90° | 870 lm |

Light technical data

| Beam angle | 24 ° |
|---------------------|--------|
| Starting time | 0.0 s |
| Warm-up time (60 %) | 0.00 s |

Dimensions & weight



| Diameter | 51.0 mm |
|------------------|---------|
| Length | 46.0 mm |
| Overall length | 45.0 mm |
| Outer bulb | MR51 |
| Maximum diameter | 51.0 mm |

Lifespan

| Nominal lamp life time | 5000 h | |
|---|--------|--|
| Rated lamp life time | 5000 h | |
| Lumen main.fact.at end of nom.life time | 0.75 | |

Additional product data

| Base (standard designation) | GU5.3 |
|-----------------------------|--------|
| Lamp mercury content | 0.0 mg |
| Mercury-free | Yes |

Capabilities

| Burning position | Any | |
|------------------|-----|--|
| Dimmable | Yes | |


Certificates & standards

| Energy efficiency class | В |
|-------------------------|--------------|
| Energy consumption | 53 kWh/1000h |

Country specific categorizations

| ILCOS | HRGS//UBIB-50-12-GU5.3-51/24 |
|-------|------------------------------|

Light Distribution



Spectral power distribution



Guarantee

Logistical Data

| Product code | Product description | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Volume | Gross weight |
|---------------|--|---------------------------------|---|----------------------|--------------|
| 4050300516691 | DECOSTAR 51 PRO 50 W 12 V 24° GU5.3 | Shipping carton box 20 | 238 mm x 122 mm x 123 mm | 3.57 dm ³ | 836.00 g |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

References / Links

For light distribution curves see

www.osram.com

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.