

## 64333 C 40-15

Halogen lamps with reflector, current-controlled, 30...40 W



### **Product benefits**

- Reduced operation and maintenance costs due to long lifetime
- Instant and constant light output over the lamp life
- Flicker-free operation
- Mercury-free

## **Product features**

- Dimmable
- Available with connector combinations A, B, C/Z on request
- Infrared radiation output that provides light in the worst of conditions





## Product datasheet

### Technical data


## **Electrical data**

Nominal wattage	40.00 W	
Lamp current	6.6 A	

### Photometrical data

Luminous intensity	10000 cd
Axial luminous intensity	12700 cd

## **Dimensions & weight**



Diameter	35.3 mm
Length	35.0 mm
Length with base excl. base pins/connection	37.00 mm

## Lifespan

Lifespan	1500 h
----------	--------

## Capabilities

Burning position	h45	
Connection with cable [AGGR]	Yes	
Mains terminals	Leads w/male flat connectors	

## **Country specific categorizations**

Order reference	64333 C 40W-15
0.00.10.00.00	0.555 0.017 25

## Country specific information

# Product datasheet

4008321104885 OSRH64333C - - -

### Product datasheet

### Safety advice

To prevent personal injury or damage to property, halogen lamps may only be operated in suitable luminaires designed with suitable mechanisms (protective shields, grids, etc.) to ensure that in the event of a lamp bursting no parts/shards can escape and that during operation no ultraviolet radiation can escape. There must also be a warning sign to indicate that the lamps give off high levels of heat. Detailed information is available on request.

#### Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4008321104885	64333 C 40-15	Folding carton box 1	50 mm x 34 mm x 34 mm	0.06 dm <sup>3</sup>	21.33 g
4008321104892	64333 C 40-15	Shipping carton box 20	191 mm x 133 mm x 85 mm	2.16 dm <sup>3</sup>	448.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

### References / Links

For more information on airfield lamps see the brochure:

"The reliable guiding stars - Effective solutions for airfield lighting: Tungsten halogen lamps and LED light sources".

#### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.