

HALOSTAR OVEN 20 W 12 V G4

HALOSTAR OVEN | Low-voltage halogen lamps with pin base for oven lighting



Areas of application

- Baking ovens

Product benefits

- Two to three times the luminous efficiency of conventional oven lighting
- Optimum halogen content for high temperatures
- Tempered pins for reliable contact at high temperatures
- Suitable for pyrolysis (permissible ambient temperature 450 °C)
- Contains no mercury



Product datasheet

Technical data

Electrical data

Nominal wattage	20.00 W
Nominal voltage	12.0 V
Rated luminous flux	320 lm
Rated wattage	20.00 W
Number of switching cycles	50000
Power factor λ	1.00


Photometrical data

Nominal luminous flux	320 lm
Color temperature	2800 K
Light color (designation)	Warm White
Color rendering index Ra	100

Light technical data

Starting time	0.0 s

Dimensions & weight



Diameter	10.0 mm
Length	33.0 mm
Overall length	31.0 mm
Light center length (LCL)	22.0 mm
Outer bulb	T10

Lifespan

Nominal lamp life time	2000 h ¹⁾
Rated lamp life time	2000 h

Product datasheet

Lumen main.fact.at end of nom.life time	0.80

 $^{^{1\!\!})}$ Average lifespan at room temperature; higher temperature can reduce the lifespan

Additional product data

Base (standard designation)	G4	
Lamp mercury content	0.0 mg	
Mercury-free	Yes	
Product remark	Heat-resistant up to 300°C/Lamp suitable for oven with high temperature self cleaning (Lamps must be switched off! Max. ambient temperature 450 °C)/For use in shielded luminaires only	

Capabilities

Burning position	Any
Dimmable	Yes

Certificates & standards

Energy efficiency class	С
Energy consumption	22 kWh/1000h

Country specific categorizations

ILCOS	HSGST/C/UB-20-12-G4-10/22

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4050300023946	HALOSTAR OVEN 20 W 12 V G4	Shipping carton box 3200	310 mm x 150 mm x 285 mm	13.25 dm³	4680.00 g
4050300308050	HALOSTAR OVEN 20 W 12 V G4	Shipping carton box 40	144 mm x 107 mm x 121 mm	1.86 dm ³	178.60 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.