## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

## Supplier's name or trade mark: OSRAM

Supplier's address: OSRAM GmbH, Nonnendammallee 44, 13629 Berlin, DE

**Model identifier:** 4008321746078

## Type of light source:

| Lighting technology used:     | HL     | Non-directional or directional: | NDLS |  |  |
|-------------------------------|--------|---------------------------------|------|--|--|
| Light source cap-type         | GX6.35 |                                 |      |  |  |
| (or other electric interface) |        |                                 |      |  |  |
| Mains or non-mains:           | MLS    | Connected light source (CLS):   | No   |  |  |
| Colour-tuneable light source: | No     | Envelope:                       | -    |  |  |
| High luminance light source:  | No     |                                 |      |  |  |
| Anti-glare shield:            | No     | Dimmable:                       | Yes  |  |  |
| Product parameters            |        |                                 |      |  |  |

| Floudet parameters                   |  |                           |   |                  |  |  |
|--------------------------------------|--|---------------------------|---|------------------|--|--|
| Parameter                            |  | Value                     | Parameter   | Value            |  |  |
| General product parameters:          |  |                           |   |                  |  |  |
| 0,                                   | mption in on-<br>000 h), rounded<br>est integer                              | 225                       | Energy efficiency<br>class  | G                |  |  |
| indicating if it i<br>in a sphere (3 | us flux (фuse),<br>refers to the flux<br>60º), in a wide<br>in a narrow cone | 5 795 in<br>Sphere (360°) | Correlated colour<br>temperature,<br>rounded to the<br>nearest 100 K,<br>or the range of<br>correlated colour<br>temperatures,<br>rounded to the<br>nearest 100 K, that<br>can be set | 3 300            |  |  |
| On-mode<br>expressed in W            | power (P <sub>on</sub> ),  | 225,0                     | Standby power (P <sub>sb</sub> ),<br>expressed in W<br>and rounded to the<br>second decimal   | 0,00             |  |  |
| for CLS, expre                       | ndby power (P <sub>net</sub> )<br>essed in W and<br>second decimal           | -                         | Colour rendering<br>index, rounded to<br>the nearest integer,<br>or the range of CRI-<br>values that can be<br>set  | 100              |  |  |
| Outer<br>dimensions<br>without       | Height   | 53                        | Spectral power  | See image        |  |  |
|                                      | Width  | 19                        | distribution in the   | in last page     |  |  |
|                                      | Depth  | 19                        |   | <br>  Page 1 / 3 |  |  |

| separate<br>control gear,<br>lighting<br>control parts<br>and non-<br>lighting<br>control parts,<br>if any<br>(millimetre) | range 250 nm to 800<br>nm, at full-load |       |
|--|---|-------|
| Claim of equivalent power <sup>(a)</sup>   | - If yes, equivalent power (W)          | -     |
|  | Chromaticity<br>coordinates (x and y)   | 0,418 |

(a)<sub>'-'</sub> : not applicable;

(b)'-' : not applicable;

