

# 64635 HLX

Halogen lamps with reflector MR16



#### Product features

- Xenon instead of krypton as the filler gas (XENOPHOT HLX versions)
- Luminous flux up to 10 % higher with same power consumption (XENOPHOT HLX versions)



March 10, 2016, 22:48:45 64635 HLX

### Technical data


#### **Electrical data**

| Nominal wattage | 150.00 W |
|-----------------|----------|
| Nominal voltage | 15.0 V   |

## Light technical data

| Focal length | 19.0 mm |
|--------------|---------|
|              |         |

## Dimensions & weight



| Diameter | 51.0 mm |
|----------|---------|
| Length   | 45.0 mm |

### Lifespan

## Additional product data

| Coating                     | Gold                                                                 |  |
|-----------------------------|----------------------------------------------------------------------|--|
| Base (standard designation) | GZ6.35                                                               |  |
| Product remark              | Infra-red lamp; temperature at the focal point approximately 1300 °C |  |


## Capabilities

| Cooling          | Forced |
|------------------|--------|
| Burning position | Any    |

### Country specific categorizations

#### Country specific information

| Product code  | METEL code   | SEG-No. | STK-Number | UK Org |
|---------------|--------------|---------|------------|--------|
| 4050300238807 | OSRH64635HLX | -       | -          | -      |



#### Logistical Data

| Product code  | Product description | Packaging unit<br>(Pieces/Unit) | Dimensions (length<br>x width x height) | Volume               | Gross weight |
|---------------|---------------------|---------------------------------|-----------------------------------------|----------------------|--------------|
| 4050300238807 | 64635 HLX           | Folding carton box<br>1         | 56 mm x 43 mm x<br>48 mm                | 0.12 dm³             | 34.00 g      |
| 4050300946443 | 64635 HLX           | Shipping carton box<br>20       | 238 mm x 122 mm x<br>123 mm             | 3.57 dm <sup>3</sup> | 836.00 g     |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

#### References / Links

For further technical information please refer to the following OSRAM brochure: "Technology and applications, Low-voltage tungsten-halogen lamps" "Halogen lamps, low and medium voltage for entertainment, technical and medical applications" cross reference list

#### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.