## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light

| sources  |                  |                            | <b></b>  | 6,           |  |
|--|------------------|----------------------------|--|--------------|--|
| Supplier's nam   | e or trade mark: | OSRAM                      |  |              |  |
| Supplier's addi  | ress: OSRAM Gmb  | oH, Nonnendammal           | lee 44, 13629 Berlin, DE   |              |  |
| Model identifie  | er: 40528990155  | 24                         |  |              |  |
| Type of light so   | ource:           |                            |  |              |  |
| Lighting techno  | ology used:      | HL                         | Non-directional or directional:  | NDLS         |  |
| Light source cap-type  |                  | GY9.5                      |  |              |  |
| (or other electric interface)  |                  |                            |  |              |  |
| Mains or non-n   | nains:           | MLS                        | Connected light source (CLS):  | No           |  |
| Colour-tuneabl   | e light source:  | No                         | Envelope:  | -            |  |
| High luminance light source:   |                  | No                         |  |              |  |
| Anti-glare shiel   | d:               | No                         | Dimmable:  | Yes          |  |
| Product parameters   |                  |                            |  |              |  |
| Parameter  |                  | Value                      | Parameter  | Value        |  |
| General product parameters:  |                  |                            |  |              |  |
| Energy consumption in on-<br>mode (kWh/1000 h), rounded<br>up to the nearest integer   |                  | 500                        | Energy efficiency class  | G            |  |
| Useful luminous flux (φuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) |                  | 12 240 in<br>Sphere (360°) | Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set | 3 193        |  |
| On-mode power (P <sub>on</sub> ), expressed in W   |                  | 500,0                      | Standby power (P <sub>sb</sub> ),<br>expressed in W<br>and rounded to the<br>second decimal  | 0,00         |  |
| Networked standby power (P <sub>net</sub> ) for CLS, expressed in W and rounded to the second decimal                                |                  | -                          | Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set   | 100          |  |
| Outer  | Height           | 90                         | Spectral power   | See image    |  |
| dimensions   | Width            | 18                         | distribution in the  | in last page |  |
| without  | Depth            | 18                         |  |              |  |

| separate control gear, lighting control parts and non- lighting control parts, if any (millimetre) | range 250 nm to 800<br>nm, at full-load |       |
|--|---|-------|
| Claim of equivalent power <sup>(a)</sup>   | - If yes, equivalent power (W)          | -     |
|  | Chromaticity coordinates (x and y)      | 0,425 |

(a)'-': not applicable; (b)'-': not applicable;

