Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

| sources | LLLGATED REGOL | -AITON (EO) 2019/2 | 015 with regard to ener | gy labelling of light |
|--|-----------------|----------------------------|--|-----------------------|
| Supplier's name | or trade mark: | OSRAM | | |
| Supplier's addre | ess: OSRAM Gmb | oH, Nonnendammal | lee 44, 13629 Berlin, DE | |
| Model identifier | r: 400832146874 | 41 | | |
| Type of light sou | ırce: | | | |
| Lighting technol | ogy used: | HL | Non-directional or directional: | NDLS |
| Light source cap-type | | G22 | | |
| (or other electric interface) | | _ | | |
| Mains or non-mains: | | MLS | Connected light source (CLS): | No |
| Colour-tuneable light source: | | No | Envelope: | - |
| High luminance light source: | | No | | |
| Anti-glare shield: | | No | Dimmable: | Yes |
| | | Product para | | |
| Parameter | | Value | Parameter | Value |
| | | General product p | | T |
| Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer | | 1 045 | Energy efficiency class | G |
| Useful luminous flux (φuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) | | 24 685 in Sphere (360°) | Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set | 3 127 |
| On-mode power (P _{on}), expressed in W | | 1 045,0 | Standby power (P _{sb}), expressed in W and rounded to the second decimal | 0,00 |
| Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal | | - | Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set | 100 |
| Outer | Height | 140 | Spectral power | See image |
| dimensions | Width | 25 | distribution in the | in last page |
| without | Depth | 25 | | Page 1 |

| separate control gear, lighting control parts and non- lighting control parts, if any (millimetre) | range 250 nm to 800 nm, at full-load | |
|--|---|-------|
| Claim of equivalent power ^(a) | - If yes, equivalent power (W) | - |
| | Chromaticity coordinates (x and y) | 0,422 |

(a)'-': not applicable; (b)'-': not applicable;

