



MASTERColour CDM-R Elite



MC CDM-R Elite 35W/930 E27 PAR20 30D

Compact, very high-efficiency, long-life Ceramic Metal Halide discharge reflector lamp producing crisp white sparkling light with high color rendering

Warnings and Safety

- \cdot Use only with electronic control gear
- · Control gear must include end-of-life protection (IEC61167, IEC 62035)
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Product data

General Information	
Cap-Base	E27 [E27]
Operating Position	UNIVERSAL [Any or Universal (U)]
Switching Cycle	1,350
Flux measurement reference	Narrow Cone
Life to 50% Failures (Nom)	15,000 hour(s)
Light Technical	
Color Code	930 [CCT of 3000K]
Beam Angle (Nom)	30 degree(s)
Luminous Flux	2,100 lumen
Luminous Intensity (Nom)	6,500 cd
Color Designation	Warm White (WW)
Chromaticity Coordinate X (Nom)	0.434
Chromaticity Coordinate Y (Nom)	0.398
Correlated Color Temperature (Nom)	3000 K

Luminous Efficacy (rated) (Nom)	61 lm/W
Color rendering index (CRI)	91
LLMF At End Of Nominal Lifetime (Nom)	80 %
Luminous Flux in 90° Cone (Rated)	2,100 lumen
Operating and Electrical	
Power Consumption	39.1 W
Warm-up time to 60% light	120 s
Voltage (Nom)	88 V
Voltage (Nom)	88 V
Controls and Dimming	
Dimmable	No
Mechanical and Housing	
Bulb Finish	Clear

Datasheet, 2023, October 17 data subject to change

MASTERColour CDM-R Elite

Bulb Shape	PAR20 [PAR 2.5 inch/63mm]
Approval and Application	
Energy Efficiency Class	G
Mercury (Hg) Content (Max)	4.7 mg
Mercury (Hg) Content (Nom)	4.7 mg
Energy Consumption kWh/1000 h	40 kWh
EPREL Registration Number	473304
Product Data	
Full product code	871829165157400


Order product name	MC CDM-R Elite 35W/930 E27 PAR20 30D	
Order code	928050300630	
Numerator - Quantity Per Pack	1	
Numerator - Packs per outer box	12	
Material Nr. (12NC)	928050300630	
Full product name	MC CDM-R Elite 35W/930 E27 PAR20 30D	
EAN/UPC - Case	8718291651581	
EAN/UPC - Product/Case	8718291651574	


Dimensional drawing

D .

Product	D (max)	C (max)
MC CDM-R Elite 35W/930 E27 PAR20 30D	65 mm	95 mm

Photometric data






Light Distribution Diagram - MC CDM-R Elite 35W/930 E27 PAR20 30D

Spectral Power Distribution Colour - MC CDM-R Elite 35W/930 E27 PAR20 30D

MASTERColour CDM-R Elite

Lifetime





Lumen Maintenance Diagram - MC CDM-R Elite 35W/930 E27 PAR20 30D

Life Expectancy Diagram - MC CDM-R Elite 35W/930 E27 PAR20 30D



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.