

PRODUCT DATASHEET HALOPIN PRO 20 W 240 V G9

PARATHOM® LINE R7s | Double-ended special LED lamps



Areas of application

- General illumination
- Workplace lighting
- Lighting for reading
- Dining table lighting
- Mirror lighting
- Accent lighting
- Mood lighting

Product benefits

- Brilliant accent lighting
- Incredibly small dimensions for revolutionary new luminaire designs
- Robust filament design thanks to innovative, unique bulb pinch technology
- Approved for use in open luminaires (to IEC 60598-1)
- UV filter
- Complies with IEC 60432-2 thanks to integrated fuse function
- Lower thermal output (compared with the standard reference product)
- The lamp shuts down reliably
- Contains no mercury

Product features

- Average life: 2,000 h
- Dimmable
- Color rendering index Ra: 100

TECHNICAL DATA

Electrical data

Nominal wattage	20 W
Nominal voltage	240.00 V
Claimed equiv. conventional lamp power	25 W
Power factor λ	1,00

Photometrical data

Luminous flux	235 lm
Luminous efficacy	11 lm/W
Lumen main.fact.at end of nom.life time	0.80
Light color (designation)	Warm White
Color temperature	2700 K
Color rendering index Ra	100
Light color	1027

Light technical data

Warm-up time (60 %)	0.00 s
Starting time	0.0 s

Dimensions & weight

Overall length	43.00 mm
Length	43.00 mm
Light center length (LCL)	22,0 mm
Diameter	14.00 mm
Maximum diameter	14 mm
Product weight	2.9 g

Lifespan

Nominal lamp life time	2000 h
Number of switching cycles	50000

Additional product data

Base (standard designation)	G9
Mercury content	0.0 mg
Mercury-free	Yes
Design / version	Tube

Capabilities

Burning position	Any	
Certificates & standards		
Energy efficiency class	D	
Energy consumption	20.00 kWh/1000h	
Country-specific categorizations		
ILCOS	HSGST/C/UB-20-240-G9-22	
Order reference	66720 ECO	

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4008321945556	Folding box 1	70 mm x 23 mm x 25 mm	6.40 g	0.04 dm³
4008321945563	Shipping box 20	144 mm x 55 mm x 118 mm	141.80 g	0.93 dm³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.