



Compact Source

6981P 750W G9.5 115V 1CT/10

The very compact filament in the Compact Source series helps create a proportionately high beam intensity and the Compact Source range is therefore ideal for the latest generation of high-performance luminaires. Also, thanks to their low energy consumption, each dimmer can serve significantly more fixtures, thereby reducing overall dimmer costs. What's more, the Compact Source lamps incorporate the innovative P3 technology, developed by Philips, which enables the lamps to be used at higher temperatures in any burning position. This results in longer lamp lifetimes, reduced lamp replacement costs, and a more consistent lighting performance over the whole lifetime of the lamp.

Product data

General Information	
Cap-Base	G9.5 [G9.5]
Philips Code	6981P
ANSI Code	-
Operating Position	UNIVERSAL [Any or Universal (U)]
Main Application	Entertainment
Life To 50% Failures (Nom)	300 h
System Description	P3 Technology
Light Technical	
Luminous Flux (Rated) (Nom)	20500 lm
Correlated Color Temperature (Nom)	3200 K
Color Rendering Index (Nom)	100
Operating and Electrical	
Power (Rated) (Nom)	750 W
Rapid Acting HBC Fuse	10 V


Voltage (Nom)	115 V
Controls and Dimming	
Dimmable	Yes
Mechanical and Housing	
Bulb Finish	Clear
Filament Shape	Bi-Plane
Filament Dimensions WxH	9.5x9.0
Luminaire Design Requirements	
Pinch Temperature (Max)	500 °C
Product Data	
Full product code	871150051957325
Order product name	6981P 750W G9.5 115V 1CT/10
EAN/UPC - Product	8711500519573
Order code	924546834428

Compact Source

Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	10
Material Nr. (12NC)	924546834428

Net Weight (Piece)	0.025 kg
--------------------	----------

Dimensional drawing



6981P 750W G9.5 115V

Product	D	H	W	L	C
6981P 750W G9.5 115V 1CT/10	19 mm	9 mm	9.5 mm	60.5 mm	104 mm

