











Discharge - CSR Turn and Lock (TAL)

CSR700/TAL/PGJX28

78718

Product information

These single-ended metal halide lamps are especially useful for moving-light applications that call for high colour temperatures and brighter light sources. The 'Turn And Lock' technology provides easy installation. A very short arc gap allows for higher beam intensity. This enables good system performance, colour stability and superior lumen maintenance over life. Easy release base (Turn And Lock) enabling quick lamp change at events- High lumen output.

Application areas



Event and Tour









Product data

PGJX28
Globe
Clear
18
112
56
4
51
111
U - Universal
General Electric (GE)

Performance data

Colour Code	747
Colour Rendering Index (CRI) [Ra]	75
Nominal correlated colour temperature (CCT) [K]	7400
Nominal lumens [lm]	50000
Energy efficiency class (EEC)	A
Nominal chromaticity coordinate X	0.3
Nominal chromaticity coordinate Y	0.31
Weighted energy consumption [kWh/1000h]	770

Electrical data

Nominal power [W]	700
Nominal lamp voltage [V]	70
Lamp Current [A]	10
Dimming Capability	Yes
Ballast Required	Yes



Discharge - CSR Turn and Lock (TAL)

CSR700/TAL/PGJX28

78718

Logistic data

DUN Code	10043168787182
EAN Code	0043168787185
Pack Quantity	4
Inner pack type	BOX
Outer pack type	OUTER BOX
Layer quantity	96 EUR, 120 UK
Layer quantity EUR	96
Layer quantity UK	120
Pallet quantity EUR (PC)	480
Pallet quantity UK (PC)	600
Outer case size	175 x 175 x 210 (mm)
Product status	Available

Downloads & Links

Go to the catalog site (HTTP)

Entertainment Solution Spectrum Catalogue (PDF)

Lighting design tools & calculators (HTTP)

High-res images / Technical drawings (HTTP)

Certificate for the Quality Management System of GE Lighting EMEA (PDF)

Certificate for the Environmental Management System of GE Lighting EMEA (PDF)

Disclaimer

Special Purpose Lamp, Not suited for household illumination