

Plusline ES Small

Plusline ES Small 118mm 2y 120W R7s 230V 1BB

Mains-voltage halogen linear lamp with superior quality and reliability. Offers very long lifetime and crisp halogen light. Ideal solution for decorative luminaires and for security or task lighting floodlights.

Product data

• General Information

Cap-Base R7S [R7s]
Operating Position UNIVERSAL [Any or Universal (U)]
Nominal Lifetime (Nom)
Switching Cycle 8000X

• Light Technical

Luminous Flux 2220 lm (Nom) Luminous Flux 2220 lm (Rated) (Nom) 2900 K Correlated Color Temperature (Nom) Luminous Efficacy 18.5 lm/W (rated) (Nom) Color Rendering 100 Index (Nom) Llmf At End Of 80 % Nominal Lifetime (Min)

• Operating and Electrical

Power (Rated) 120.0 W
(Nom)
Lamp Current (Nom) 0.52 A
Wattage Equivalent 150 W
Starting Time (Nom) 0.0 s
Warm Up Time To
60% Light (Nom)
Power Factor (Nom) 1
Voltage (Nom) 230 V

Controls and Dimming

Dimmable Yes

Mechanical and Housing

Bulb Finish Clear (CL)

• Approval and Application

Energy Efficiency D Label (EEL) Energy Consumption 120 kWh kWh/1000 h

• Luminaire Design Requirements


Bulb Temperature 900 °C (Max)
Pinch Temperature 350 °C (Max)

• Product Data

872790085216500 Full product code Plusline ES Small 118mm 2y 120W Order product name R7s 230V 1BB EAN/UPC - Product 8727900852165 924587444210 Order code Numerator - Quantity Per Pack Numerator - Packs 100 per outer box Material Nr. (12NC) 924587444210 Net Weight (Piece) 9.000 g



Dimensional drawing



DESmall 118mm 2y 120W R7s 230V T11 CL

Product	D	В	В	В	C
Plusline ES Small 118mm 2y 120W R7s 230V	11 mm	115.8 mm	114.2 mm	112.6 mm	118 mm
1BB					





 $\ \odot$ 2015 Philips Lighting Holding B.V. All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. (Royal Philips) or their respective owners.