



MASTER SON-T APIA Plus Xtra



MST SON-T APIA Plus Xtra 250W E40 1SL/12

High Pressure Sodium lamp with clear tubular outer bulb shape, high output and longest reliable lifetime

Warnings and Safety

- Control gear must include end-of-life protection (IEC60662, IEC 62035)
- HF gear must comply with Philips LDi guideline
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Product data

| General Information | |
|------------------------------------|----------------------------------|
| Cap-Base | E40 [E40] |
| Operating Position | UNIVERSAL [Any or Universal (U)] |
| Flux measurement reference | Sphere |
| Life to 50% Failures (Nom) | 45,000 hour(s) |
| Light Technical | |
| Color Code | - [Not Specified] |
| Luminous Flux | 33,700 lumen |
| Chromaticity Coordinate X (Nom) | 0.535 |
| Chromaticity Coordinate Y (Nom) | 0.42 |
| Correlated Color Temperature (Nom) | 2000 K |
| Luminous Efficacy (rated) (Nom) | 132 lm/W |
| Color rendering index (CRI) | - |


| Operating and Electrical | |
|----------------------------|--------------|
| Power Consumption | 255.0 W |
| Voltage (Nom) | 99 V |
| Voltage (Nom) | 99 V |
| Controls and Dimming | |
| Dimmable | Yes |
| Mechanical and Housing | |
| Bulb Finish | Clear |
| Bulb Shape | T46 [T 46mm] |
| Approval and Application | |
| Energy Efficiency Class | E |
| Mercury (Hg) Content (Max) | 15.1 mg |
| Mercury (Hg) Content (Nom) | 15.1 mg |

MASTER SON-T APIA Plus Xtra

| | |
|-------------------------------|--|
| Energy Consumption kWh/1000 h | 255 kWh |
| EPREL Registration Number | 473377 |
| Product Data | |
| Full product code | 872790092737500 |
| Order product name | MST SON-T APIA Plus Xtra 250W E40 1SL/12 |
| Order code | 928150419230 |
| Numerator - Quantity Per Pack | 1 |


| | |
|---------------------------------|--|
| Numerator - Packs per outer box | 12 |
| Material Nr. (12NC) | 928150419230 |
| Full product name | MST SON-T APIA Plus Xtra 250W E40 1SL/12 |
| EAN/UPC - Case | 8727900927382 |
| EAN/UPC - Product/Case | 8727900927375 |

Dimensional drawing




| Product | D (max) | O | L | C (max) |
|--|---------|-------|--------|---------|
| MST SON-T APIA Plus Xtra 250W E40 1SL/12 | 48 mm | 65 mm | 158 mm | 257 mm |

Photometric data




Light Distribution Diagram - MST SON-T APIA Plus Xtra 250W E40 1SL/12




Spectral Power Distribution Colour - MST SON-T APIA Plus Xtra 250W E40 1SL/12

MASTER SON-T APIA Plus Xtra

Lifetime



Life Expectancy Diagram - MST SON-T APIA Plus Xtra 250W E40 1SL/12



Lumen Maintenance Diagram - MST SON-T APIA Plus Xtra 250W E40 1SL/12

