











Discharge - Single Ended Hot Restrike CSR12000/SE/HR/UV-C

97272

# **Product information**

Compact, single ended metal halide hot restrike lamps for a variety of applications requiring high luminance, reliability and excellent colour characteristics. Excellent colour rendering, Ra>90, and high CCT 5600–6000 K with superior colour stability- Universal burn position with hot restrike capability- High efficiency with excellent lumen maintenance -Available with UV blocking.

#### **Application areas**



Film and Broadcast







97272

# **Product data**

Cap/Base	G38
Bulb Shape	Tubular
Bulb Finish	Clear
Light Center Length [mm]	255
Net weight per piece [g]	1200
Gross weight per piece [g]	2600
Operating position	U - Universal
Brand	General Electric (GE)

## Performance data

Colour Rendering Index (CRI) [Ra]	90
Nominal correlated colour temperature (CCT) [K]	6000
Nominal lumens [lm]	1150000
Energy efficiency class (EEC)	A+
Nominal chromaticity coordinate X	0.3
Nominal chromaticity coordinate Y	0.3
Weighted energy consumption [kWh/1000h]	13200

## **Electrical data**

Nominal power [W]	12000
Nominal lamp voltage [V]	160
Dimming Capability	Yes



# Discharge - Single Ended Hot Restrike CSR12000/SE/HR/UV-C

97272

#### Logistic data

DUN Code	10043168972724
EAN Code	0043168972727
Pack Quantity	4
Inner pack type	BOX
Outer pack type	OUTER BOX
Layer quantity	8 UK
Layer quantity UK	8
Pallet quantity UK (PC)	8
Outer case size	540 x 540 x 610 (mm)
Product status	Available

#### **Downloads & Links**

Go to the catalog site (HTTP)

**Entertainment Solution Spectrum Catalogue (PDF)** 

Lighting design tools & calculators (HTTP)

High-res images / Technical drawings (HTTP)

Certificate for the Quality Management System of GE Lighting EMEA (PDF)

Certificate for the Environmental Management System of GE Lighting EMEA (PDF)

#### Disclaimer

Special Purpose Lamp, Not suited for household illumination