



MASTERColour CDM-T Elite



MASTERC CDM-T Elite 100W/930 G12 1CT/12

Single-ended, very high-efficiency, long-life Ceramic Metal Halide discharge lamp producing crisp white sparkling light with high color rendering

Warnings and Safety

- Use only in totally enclosed luminaire, even during testing (IEC61167, IEC 62035, IEC60598)
- The luminaire must be able to contain hot lamp parts if the lamp ruptures
- \cdot Use only with electronic control gear. 35W & 70W lamps may also use electromagnetic gear.
- · Control gear must include end-of-life protection (IEC61167, IEC 62035)
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Product data

General Information	
Cap-Base	G12 [G12]
Operating Position	UNIVERSAL [Any or Universal (U)]
Flux measurement reference	Sphere
Life to 50% Failures (Nom)	20,000 hour(s)
Light Technical	
Color Code	930 [CCT of 3000K]
Luminous Flux	11,000 lumen
Color Designation	Warm White (WW)
Chromaticity Coordinate X (Nom)	0.434
Chromaticity Coordinate Y (Nom)	0.398
Correlated Color Temperature (Nom)	3000 K
Luminous Efficacy (rated) (Nom)	110 lm/W

Color rendering index (CRI)	92
Operating and Electrical	
Power Consumption	100.1 W
Voltage (Nom)	88 V
Voltage (Nom)	88 V
Controls and Dimming	
Dimmable	No
Mechanical and Housing	
Bulb Finish	Clear
Bulb Shape	T19 [T 19mm]


Datasheet, 2023, October 9 data subject to change

MASTERColour CDM-T Elite

Approval and Application	
Energy Efficiency Class	F
Mercury (Hg) Content (Max)	10.1 mg
Mercury (Hg) Content (Nom)	10.1 mg
Energy Consumption kWh/1000 h	101 kWh
EPREL Registration Number	473251
Product Data	
Full product code	872790087169200
Order product name	MASTERC CDM-T Elite 100W/930 G12 1CT/12

Order code	928183205125
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	12
Material Nr. (12NC)	928183205125
Full product name	MASTERC CDM-T Elite 100W/930 G12 1CT/12
EAN/UPC - Case	8727900871708
EAN/UPC - Product/Case	8727900871692

Dimensional drawing





 Product
 D (max)
 D (max)
 L (min)
 L (max)
 L (max)
 C (max)


 MASTERC CDM-T Elite 100W/930
 20 mm
 8.5 mm
 55 mm
 57 mm
 56 mm
 110 mm

 G12 1CT/12

Photometric data








Light Distribution Diagram - MASTERC CDM-T Elite 100W/930 G12 1CT/12

Spectral Power Distribution Colour - MASTERC CDM-T Elite 100W/930 G12 1CT/12

MASTERColour CDM-T Elite

Lifetime





Life Expectancy Diagram - MASTERC CDM-T Elite 100W/930 G12 1CT/12

Lumen Maintenance Diagram - MASTERC CDM-T Elite 100W/930 G12 1CT/12



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.