



MASTERColour CDM-T



MASTERC CDM-T 35W/830 G12 1CT/12

Range of single-ended, compact, high-efficiency, discharge lamps with a stable color over lifetime and a crisp, sparkling light

Warnings and Safety

- Use only in totally enclosed luminaire, even during testing (IEC61167, IEC 62035, IEC60598)
- $\boldsymbol{\cdot}$ The luminaire must be able to contain hot lamp parts if the lamp ruptures
- \cdot Control gear must include end-of-life protection (IEC61167, IEC 62035)
- Lamps may use electronic or electromagnetic control gear, except 35W/942 and 20W lamps, which must use electronic control gear.
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Product data

2 [G12]			
NIVERSAL [Any or Universal (U)]			
Sphere			
12,000 hour(s)			
0 [CCT of 3000K]			
100 lumen			
arm White (WW)			
434			
398			
000 K			

Luminous Efficacy (rated) (Nom)	79 lm/W
Color rendering index (CRI)	83
Operating and Electrical	
Power Consumption	39.1 W
Voltage (Nom)	82 V
Voltage (Nom)	82 V
Controls and Dimming	
Dimmable	No
Mechanical and Housing	
Bulb Finish	Clear


Datasheet, 2023, October 17 data subject to change

MASTERColour CDM-T

Bulb Shape	T19 [T 19mm]				
Approval and Application					
Energy Efficiency Class	G				
Mercury (Hg) Content (Max)	3.2 mg				
Mercury (Hg) Content (Nom)	3.1 mg				
Energy Consumption kWh/1000 h	40 kWh				
EPREL Registration Number	473333				
Product Data					
Full product code	871150019697215				

Order product name	MASTERC CDM-T 35W/830 G12 1CT/12			
Order code	928083105125			
Numerator - Quantity Per Pack	1			
Numerator - Packs per outer box	12			
Material Nr. (12NC)	928083105125			
Full product name	MASTERC CDM-T 35W/830 G12 1CT/12			
EAN/UPC - Case	8711500196989			
EAN/UPC - Product/Case	8711500196972			


Dimensional drawing




Product	D (max)	D	0	L (min)	L (max)	L	C (max)
MASTERC CDM-T	20 mm	0.75 inch	5 mm	55 mm	57 mm	56 mm	103 mm
35W/830 G12 1CT/12							

Photometric data









Light Distribution Diagram - MASTERC CDM-T 35W/830 G12 1CT/12

Spectral Power Distribution Colour - MASTERC CDM-T 35W/830 G12 1CT/12

MASTERColour CDM-T

Lifetime





Lumen Maintenance Diagram - MASTERC CDM-T 35W/830 G12 1CT/12

Life Expectancy Diagram - MASTERC CDM-T 35W/830 G12 1CT/12



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.