



# MASTERColour CDM-TD



# MASTERC CDM-TD 70W/942 RX7s 1CT/12

Range of double-ended, compact, high-efficiency, discharge lamps with a stable color over lifetime and a crisp, sparkling light

#### **Warnings and Safety**

- · Use only in totally enclosed luminaire, even during testing (IEC61167, IEC 62035, IEC60598)
- $\boldsymbol{\cdot}$  The luminaire must be able to contain hot lamp parts if the lamp ruptures
- $\boldsymbol{\cdot}$  Lamps may use electronic or electromagnetic control gear
- · Control gear must include end-of-life protection (IEC61167, IEC 62035)
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

#### **Product data**

| General Information                   |  |  |  |  |  |
|---------------------------------------|--|--|--|--|--|
| Cap-Base                              | RX7S [RX7s]                              |  |  |  |  |
| Operating Position                    | P45 [Parallel +/-45D or Horizontal(HOR)] |  |  |  |  |
| Flux measurement reference            | Sphere                                   |  |  |  |  |
| Life to 50% Failures (Nom)            | 16,000 hour(s)                           |  |  |  |  |
|                                       |  |  |  |  |  |
| Light Technical                       |  |  |  |  |  |
| Color Code                            | 942 [CCT of 4200K]                       |  |  |  |  |
| Luminous Flux                         | 5,450 lumen                              |  |  |  |  |
| Color Designation                     | Cool White (CW)                          |  |  |  |  |
| Chromaticity Coordinate X (Nom)       | 0.371                                    |  |  |  |  |
| Chromaticity Coordinate Y (Nom)       | 0.366                                    |  |  |  |  |
| Correlated Color Temperature (Nom)    | 4200 K                                   |  |  |  |  |
| Luminous Efficacy (rated) (Nom)       | 76 lm/W                                  |  |  |  |  |
| · · · · · · · · · · · · · · · · · · · | · · · · · · · · · · · · · · · · · · ·    |  |  |  |  |

| 92           |
|--------------|
|              |
|              |
| 71.5 W       |
| 90 V         |
| 90 V         |
|              |
|              |
| No           |
|              |
|              |
| Clear        |
| T22 [T 22mm] |
|              |

Datasheet, 2023, October 23 data subject to change

# **MASTERColour CDM-TD**

| Approval and Application      |                                    |  |  |  |  |
|-------------------------------|------------------------------------|--|--|--|--|
| Energy Efficiency Class       | G                                  |  |  |  |  |
| Mercury (Hg) Content (Max)    | 4.7 mg                             |  |  |  |  |
| Mercury (Hg) Content (Nom)    | 4.8 mg                             |  |  |  |  |
| Energy Consumption kWh/1000 h | 72 kWh                             |  |  |  |  |
| EPREL Registration Number     | 473339                             |  |  |  |  |
|                               |                                    |  |  |  |  |
| Product Data                  |                                    |  |  |  |  |
| Full product code             | 871150020002015                    |  |  |  |  |
| Order product name            | MASTERC CDM-TD 70W/942 RX7s 1CT/12 |  |  |  |  |

| Order code                      | 928084705133                       |
|---------------------------------|------------------------------------|
| Numerator - Quantity Per Pack   | 1                                  |
| Numerator - Packs per outer box | 12                                 |
| Material Nr. (12NC)             | 928084705133                       |
| Full product name               | MASTERC CDM-TD 70W/942 RX7s 1CT/12 |
| EAN/UPC - Case                  | 8711500200037                      |
| EAN/UPC - Product/Case          | 8711500200020                      |
|                                 |                                    |

# Dimensional drawing



| Product                            | D (max) | D         | 0    | C (max)   |
|------------------------------------|---------|-----------|------|-----------|
| MASTERC CDM-TD 70W/942 RX7s 1CT/12 | 22 mm   | 0.75 inch | 7 mm | 119.63 mm |

### Photometric data









#### Light Distribution Diagram - MASTERC CDM-TD 70W/942 RX7s 1CT/12

Spectral Power Distribution Colour - MASTERC CDM-TD 70W/942 RX7s 1CT/12

# **MASTERColour CDM-TD**

#### Lifetime





Life Expectancy Diagram - MASTERC CDM-TD 70W/942 RX7s 1CT/12

Lumen Maintenance Diagram - MASTERC CDM-TD 70W/942 RX7s 1CT/12



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.