

DALI REP SO | Signal repeaters for LMS



Areas of application

- Large luminaire groups

Product benefits

- The ECGs connected to the repeater operate as a group
- Disconnection of ECG standby power via integrated load contact
- Can be addressed via DALI
- Cascadable

Product features


- Expansion of DALI systems by 64 ECGs each time
- Extends the DALI line by 300 m
- Touch DIM control of 64 DALI ECGs
- Maximum power consumption in stand-by mode: 1 W

Technical data

Electrical data

Nominal voltage	100...240 V
Mains frequency	50/60 Hz
System wattage	5.50 W

Dimensions & weight



Length	96.0 mm
Width	72.0 mm
Height	62.0 mm
Product weight	150.00 g

Temperatures & operating conditions

Ambient temperature range	0...+50 °C
---------------------------	------------


Capabilities

Dimming interface	DALI
Number of control outputs	1
Type of installation	DIN rail mounting

Certificates & standards

Type of protection	IP20
Protection class	I

Download Data

File	
	Brochures Non-system-specific components brochure

Product datasheet



Declarations of conformity
Declaration of conformity DALI Repeater



Installation/Operation notice
Technical instructions

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4008321301093		Shipping carton box 16	371 mm x 179 mm x 232 mm	15.41 dm ³	3112.20 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.