
DULUX T PLUS 18 W/827

OSRAM DULUX T PLUS | CFLni, 3 tubes, with 2-pin base for CCG operation



Areas of application

- Offices, public buildings
- Shops
- Supermarkets and department stores
- Hotels, restaurants
- Industrial lighting

Product benefits

- Very economical
- Good quality of light
- Excellent luminous flux
- Long service life
- Improved maintenance

Product features

- Average life: 10,000 h
- Color rendering index R_a : 80...89
- Short and compact pin-base lamp with triple-turn tubes
- Single-ended two-pin plug-in GX24d base



Product datasheet

Technical data


Electrical data

Nominal wattage	18.00 W
Rated wattage	18.00 W
Rated luminous flux	1200 lm

Photometrical data

Nominal luminous flux	1200 lm
Light color (designation)	LUMILUX INTERNA
Luminous flux at 25 °C	1200 lm
Color temperature	2700 K
Color rendering index Ra	80...89
Rated LLMF at 2,000 h	0.85
Rated LLMF at 4,000 h	0.78
Rated LLMF at 6,000 h	0.76
Rated LLMF at 8,000 h	0.75

Dimensions & weight



Diameter	11.0 mm
Overall length	122.0 mm
Length	124.0 mm
Length acc. to IEC standard	110 mm
Length with base excl. base pins/connection	101.00 mm
Outer bulb	T11X3
Maximum diameter	11.0 mm

Lifespan

Nominal lamp life time	10000 h
------------------------	---------

Product datasheet

Rated lamp life time	10000 h
Service life	6500 h
Rated lamp survival factor at 2,000 h	0.99
Rated lamp survival factor at 4,000 h	0.99
Rated lamp survival factor at 6,000 h	0.95
Rated lamp survival factor at 8,000 h	0.81
Operation mode LLMF/LSF	50 Hz
Lifespan	10000 h ¹⁾

¹⁾ With CCG/LLCG

Additional product data

Base (standard designation)	GX24d-2
Lamp mercury content	1.7 mg
Product remark	Suitable only for operation with 0.22 A control gear


Certificates & standards

Energy efficiency class	B
Energy consumption	23 kWh/1000h

Country specific categorizations

ILCOS	FSM-18/827-I-GX24d-2
-------	----------------------

Light Distribution



Spectral power distribution


Equipment / Accessories

- Suitable for operation on conventional control gear
- Suitable for 0.22 A control gear only (DULUX T 18 W PLUS)

Safety advice

In case of lamp breakage: www.osram.com/brokenlamp

Product datasheet



Circuit diagram

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4050300333502	DULUX T PLUS 18 W/827	Shipping carton box 10	240 mm x 128 mm x 123 mm	3.78 dm ³	832.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.