

# Lok-it! HTI 700 W/75/P50

Lok-it! | Metal halide lamps



### Product benefits

- Lamp and holder from a single source

- Rapid relamping with bayonet lock

#### **Product features**

- eXtreme Seal technology for discharge lamps



August 10, 2016, 04:00:59 Lok-it! HTI 700 W/75/P50

### Technical data


### **Electrical data**

Nominal wattage	700.00 W
Nominal voltage	100 V
Lamp voltage	100 V
Nominal current	10.0 A
Lamp current	10.0 A

### Photometrical data

Nominal luminous flux	50000 lm
Color temperature	7500 К
Color rendering index Ra	85

# Dimensions & weight



Diameter		18.0 mm					
Length		128.0 mm					
Light center length (LCL)	)	65.0 mm					
Electrode gap cold		4.0 mm					
Lifespan							
Lifespan		750 h					
Certificates & standa	ırds						
EEI – Energy Label		В					
Country specific information							
Product code	METEL code	SEG-No.	STK-Number	UK Org			

\_

4008321485205 OSRHTI700LOKP50

-

-

-

#### Safety advice

Because of their high luminance, UV radiation and high internal pressure during operation, Lok-it! lamps may only be operated in enclosed lamp casings specially constructed for the purpose. Appropriate filters must ensure that UV radiation is reduced to an acceptable level. Mercury is released if the lamp breaks. Special safety precautions must be taken. Information on safety and handling is available on request or can be found in the leaflet included with the lamp or in the operating instructions.

#### Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4008321485205	Lok-it! HTI 700 W/75/P50	Shipping carton box 1	305 mm x 82 mm x 115 mm	2.88 dm³	289.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

#### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.