

# LF-LTS -COVER-DIFF

LINEARlight FLEX | - Accessories




### **Product benefits**

- Simple installation, no tools or soldering required (CONNECT system)
- Reduced installation time (CONNECTsystem)
- Low profile (CONNECTsystem)
- Extremely vibration-proof (CONNECTsystem)
- Permissible operating temperature perfectly matched to module (CONNECTsystem)
- Can be connected to the front of the module or at division points (CONNECTsystem)

# Product datasheet

#### Technical data

# **Dimensions & weight**



Height	24.0 mm
Length	2100 mm
Width	17.7 mm

#### Download Data

#### File



Product Family Datasheet
LINEARLIGHT FLEX SLIM TRACK SYSTEM - LF-LTS

# Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4008321979001	LF-LTS -COVER-DIFF	Shipping carton box 40	2110 mm x 160 mm x 80 mm	27.01 dm³	9824.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

#### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.