



MSR Gold™ FastFit

MSR Gold 2000 FastFit 1CT/8

All lamps burn out eventually, but when this happens with single ended MSR Gold™ FastFit, it is replaced in seconds – thanks to the specially designed lamp base and lamp holder. This lamp provides a high beam intensity of pure, white light for a truly illuminating performance, while the gold-plated caps provide superior heat protection and prevent premature failure. P3 technology allows use in any position and at higher temperatures, further extending lamp life and consistency of high-quality light output. Also, because the FastFit design is applied to Philips Halogen lamps, switching between lamp technologies can be done quickly and easily. The Philips MSR Gold™ FastFit can be operated in a lamp wattage range between 700W and 2500W.

Warnings and Safety

- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Product data

| General Information | |
|------------------------------------|----------------------------------|
| Cap-Base | PGJX50 [PGJX50] |
| Operating Position | UNIVERSAL [Any or Universal (U)] |
| Life to 50% Failures (Nom) | 750 hour(s) |
| Light Technical | |
| Color Code | - [Not Specified] |
| Luminous Flux (Min) | 162,000 lumen |
| Luminous Flux | 180,000 lumen |
| Chromaticity Coordinate X (Nom) | 321 |
| Chromaticity Coordinate Y (Nom) | 332 |
| Correlated Color Temperature (Nom) | 6050 K |

| Luminous Efficacy (rated) (Nom) | 90 lm/W |
|---------------------------------|-----------------|
| Color rendering index (CRI) | 91 |
| Operating and Electrical | |
| Power Consumption | 2,000 W |
| Lamp Current (Nom) | 15.2 A |
| Controls and Dimming | |
| Dimmable | Yes |
| Product Data | |
| Full product code | 872790091949300 |

MSR Gold™ FastFit

| | |
|---------------------------------|-----------------------------|
| Order product name | MSR Gold 2000 FastFit 1CT/8 |
| Order code | 928176905114 |
| Numerator - Quantity Per Pack | 1 |
| Numerator - Packs per outer box | 8 |
| Material Nr. (12NC) | 928176905114 |

| | |
|------------------------|-----------------------------|
| Full product name | MSR Gold 2000 FastFit 1CT/8 |
| EAN/UPC - Case | 8727900919509 |
| EAN/UPC - Product/Case | 8727900919493 |

Dimensional drawing



| Product | D (max) | O | L (min) | L (max) | L | C (max) | F |
|-----------------------------|---------|--------|---------|---------|-------|---------|-------|
| MSR Gold 2000 FastFit 1CT/8 | 34 mm | 8.0 mm | 66 mm | 68 mm | 67 mm | 134 mm | 50 mm |

