



MSR Gold™ MiniFastFit (Touring/ Stage)

MSR Gold 700/1 MiniFastFit 1CT/4

Thanks to the specially designed lamp base, the MSR Gold™ MiniFastFit takes just seconds to replace, to help ensure non-stop clubbing entertainment. In addition, the innovative gold plated pins ensure excellent current transfer to prolong lamp and lamp holder lifetimes and thereby reduce lamp replacement costs. Easy handling and small compact fixture designs are allowed by the lamps compact size, while the very short arc provides a high perceived brightness and high beam intensity.

Warnings and Safety

• A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Product data

General Information						
Cap-Base	PGJX28 [PGJX28]					
Operating Position	UNIVERSAL [Any or Universal (U)]					
Life to 50% Failures (Nom)	750 hour(s)					
Light Technical						
Color Code	1					
Luminous Flux	53,400 lumen					
Chromaticity Coordinate X (Nom)	328					
Chromaticity Coordinate Y (Nom)	335					
Correlated Color Temperature (Nom)	5700 K					

Luminous Efficacy (rated) (Nom)	76.3 lm/W				
Color rendering index (CRI)	73				
Operating and Electrical					
Power Consumption	700 W				
Lamp Current (Nom)	10.2 A				
Controls and Dimming					
Dimmable	Yes				


Datasheet, 2023, October 6 data subject to change

MSR Gold™ MiniFastFit (Touring/Stage)

Product Data					
Full product code	871829169663600				
Order product name	MSR Gold 700/1 MiniFastFit 1CT/4				
Order code	928197405115				
Numerator - Quantity Per Pack	1				
Numerator - Packs per outer box	4				

Material Nr. (12NC)	928197405115
Full product name	MSR Gold 700/1 MiniFastFit 1CT/4
EAN/UPC - Case	8718291696643
EAN/UPC - Product/Case	8718291696636

Dimensional drawing



Product	D	0	L (min)	L (max)	L	С	F (max)	F	F (min)
	(max)					(max)			
MSR Gold	23.2	3.8	55 mm	57 mm	56	112 mm	36.5	36	35.3
700/1	mm	mm			mm		mm	mm	mm
MiniFastFit									
1CT/4									

