



# MASTER PL-C 2 Pin

## MASTER PL-C 26W/840/2P 1CT/5X10BOX

MASTER PL-C is an efficient medium-wattage compact fluorescent lamp, typically used in general downlights for retail, hospitality and office applications. The original Philips-invented bridge technology guarantees optimum performance in the application, enabling more light and higher efficacy than the bended technology. The 2-pin version is designed for operation on electromagnetic gear and is provided with a plug-in/pull-out lamp base.

### Product data

General Information			
Cap-Base	G24D-3 [ G24d-3]	LLMF 6000 h Rated	83 %
Life To 10% Failures (Nom)	6500 h	LLMF 8000 h Rated	81 %
Life To 50% Failures (Nom)	10000 h	Operating and Electrical	
LSF 2000 h Rated	99 %	Power (Rated) (Nom)	26.5 W
LSF 4000 h Rated	98 %	Lamp Current (Nom)	0.335 A
LSF 6000 h Rated	92 %	Temperature	
LSF 8000 h Rated	78 %	Design Temperature (Nom)	28 °C
Light Technical		Controls and Dimming	
Color Code	840 [ CCT of 4000K]	Dimmable	No
Luminous Flux (Nom)	1800 lm	Mechanical and Housing	
Luminous Flux (Rated) (Nom)	1800 lm	Cap-Base Information	2 Pins
Color Designation	Cool White (CW)	Approval and Application	
Chromaticity Coordinate X (Nom)	380	Energy Efficiency Label (EEL)	B
Chromaticity Coordinate Y (Nom)	380	Mercury (Hg) Content (Nom)	1.4 mg
Correlated Color Temperature (Nom)	4000 K	Energy Consumption kWh/1000 h	32 kWh
Luminous Efficacy (rated) (Nom)	68 lm/W		
Color Rendering Index (Nom)	82		
LLMF 2000 h Rated	92 %		
LLMF 4000 h Rated	87 %		

MASTER PL-C 2 Pin


Product Data	
Full product code	871150062100900
Order product name	MASTER PL-C 26W/840/2P 1CT/5X10BOX
EAN/UPC - Product	8711500621009
Order code	927906184001
Numerator - Quantity Per Pack	1

Numerator - Packs per outer box	50
Material Nr. (12NC)	927906184001
Net Weight (Piece)	64.300 g
ILCOS Code	FSQ-26/40/1B-I-G24d=3

Warnings and Safety

- Use only with electromagnetic control gear
- Lamp light technical and electrical characteristics are influenced by operating conditions, i.e. lamp ambient temperature and operating position
- Dimming is not possible
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.


Dimensional drawing




PL-C 26W/840/2P

Product	D (max)	D1 (max)	A (max)	B (max)	C (max)
MASTER PL-C 26W/840/2P 1CT/ 5X10BOX	27.1 mm	27.1 mm	130.5 mm	149.0 mm	171.4 mm

Photometric data



Lightcolor /840



Lightcolor /840

## MASTER PL-C 2 Pin

