

# PRODUCT DATASHEET SIG 1534

Standard high-voltage lamps, road traffic | Standard high-voltage lamps, road traffic



### Areas of application

- Road traffic signalling systems

# **TECHNICAL DATA**

# Electrical data

Nominal wattage	40 W
Nominal voltage	230240 V
Power factor $\lambda$	1,00

# Photometrical data

Luminous flux	230 lm
Luminous efficacy	5 lm/W
Color temperature	2700 K
Color rendering index Ra	100
Light color	1027

# Light technical data

Starting time	0 s

# Dimensions & weight

Overall length	107.00 mm
Length	107.00 mm
Light center length (LCL)	69,0 mm <sup>1)</sup>
Diameter	62 mm
Maximum diameter	61 mm
Product weight	31.5 g

<sup>1)</sup> Distance from the coil to the top of base

# Lifespan

	Nominal lamp life time	8000 h
_		

# Additional product data

Base (standard designation)	E27
Mercury content	0.0 mg
Mercury-free	Yes
Product remark	Not for new designs

# **Capabilities**

Burning position	s135

### Certificates & standards

Energy efficiency class	E

Energy consumption	40.00 kWh/1000h
Country-specific categoriza	ns
Order reference	1534

### Safety advice

- Use only in signal equipment/luminaires that are specially designed for the purpose. Protect the lamps against moisture during operation and installation.

### **LOGISTICAL DATA**

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4050300219288	Folding box 1	104 mm x 58 mm x 58 mm	42.10 g	0.35 dm <sup>3</sup>
4050300219295	Shipping box 100	596 mm x 222 mm x 301 mm	4618.00 g	39.83 dm³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

### **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.