

PRODUCT DATASHEET

SIG 1534 LL

Standard high-voltage lamps, road traffic | Standard high-voltage lamps, road traffic



Areas of application

- Road traffic signalling systems

TECHNICAL DATA**Electrical data**

Nominal wattage	40 W
Nominal voltage	235 V
Power factor λ	1,00

Photometrical data

Luminous flux	230 lm
Luminous efficacy	5 lm/W
Color temperature	2700 K
Color rendering index Ra	100
Light color	1027

Light technical data

Starting time	0 s
---------------	-----

Dimensions & weight

Overall length	107.00 mm
Length	107.00 mm
Light center length (LCL)	69,0 mm ¹⁾
Diameter	62 mm
Maximum diameter	61 mm
Product weight	31.5 g

¹⁾ Distance from the coil to the top of base

Lifespan

Nominal lamp life time	15000 h
------------------------	---------

Additional product data

Base (standard designation)	E27
Mercury content	0.0 mg
Mercury-free	Yes
Product remark	Not for new designs

Capabilities

Burning position	≤135
------------------	------

Certificates & standards

Energy efficiency class	E
-------------------------	---

Energy consumption	40.00 kWh/1000h
--------------------	-----------------

Country-specific categorizations

Order reference	1534 LL
-----------------	---------

Safety advice

- Use only in signal equipment/luminaires that are specially designed for the purpose. Protect the lamps against moisture during operation and installation.

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4008321044396	Unpacked 1	45 mm x 31 mm x 31 mm	37.00 g	0.04 dm ³
4052899397491	Shipping box 60	480 mm x 404 mm x 187 mm	2316.00 g	36.26 dm ³
4050300613703	Shipping box 100	400 mm x 381 mm x 264 mm	3965.00 g	40.23 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.