# **PHILIPS** Lighting

### G A G

## MASTER TL-D Super 80

#### MASTER TL-D Super 80 1m 36W/840 SLV/25

The MASTER TL-D Super 80 lamp offers more lumens per watt and better color rendering than TL-D standard colors. Furthermore, it has a lower mercury content. The lamp can be operated in existing TL-D luminaires.

#### Warnings and Safety

• A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

#### **Product data**

General Information		Lamp Current (Nom)	0.560 A
Cap-Base	G13 [Medium Bi-Pin Fluorescent]		
Flux measurement reference	Sphere	Controls and Dimming	
Life to 50% Failures (Nom)	15,000 hour(s)	Dimmable	Yes
Light Technical		Mechanical and Housing	
Color Code	840 [CCT of 4000K]	Bulb Shape	T8 [26 mm (T8)]
Luminous Flux	3,100 lumen		
Color Designation	Cool White (CW)	Approval and Application	
Chromaticity Coordinate X (Nom)	0.38	Energy Efficiency Class	G
Chromaticity Coordinate Y (Nom)	0.38	Mercury (Hg) Content (Nom)	1.7 mg
Correlated Color Temperature (Nom)	4000 K	Energy Consumption kWh/1000 h	37 kWh
Luminous Efficacy (rated) (Nom)	86 lm/W	EPREL Registration Number	423418
Color rendering index (CRI)	80		
		Product Data	
Operating and Electrical		Full product code	871150055877040
Power Consumption	36.6 W	Order product name	MASTER TL-D Super 80 1m 36W/840 SLV/25


#### **MASTER TL-D Super 80**

Order code	927923084014		
Numerator - Quantity Per Pack	1		
Numerator - Packs per outer box	25		
Material Nr. (12NC)	927923084014		
Full product name	MASTER TL-D Super 80 1m 36W/840 SLV/25		


EAN/UPC - Case	8711500558787	
EAN/UPC - Product/Case	8711500558770	

#### Dimensional drawing

Product	D (max)	A (max)	B (max)	B (min)	C (max)
MASTER TL-D Super 80 1m	28 mm	970.0 mm	977.1 mm	974.7 mm	984.2 mm
36W/840 SLV/25					




#### Photometric data




Spectral Power Distribution Colour - MASTER TL-D Super 80 1m 36W/840 SLV/25

#### Lifetime




Life Expectancy Diagram - MASTER TL-D Super 80 1m 36W/840 SLV/25



Life Expectancy Diagram - MASTER TL-D Super 80 1m 36W/840 SLV/25

#### **MASTER TL-D Super 80**

Lifetime



Lumen Maintenance Diagram - MASTER TL-D Super 80 1m 36W/840 SLV/25



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.

www.lighting.philips.com 2023, October 20 - data subject to change