



Actinic BL TL(-K) / TL-D(-K)

Actinic BL TL 6W/10 1FM/10X25CC

With an optimized spectrum matching the eye sensitivity of the housefly, Actinic BL TL(-K)/TL-D(-K)/TL-E/PL-S and PL-L lamps are perfect for attracting insects. They have virtually no UV-B output, and so are perfectly safe. What's more, with the lowest mercury content in the industry and being 100% lead-free, these lamps represent a very good environmental choice. Furthermore, the availability of a wide range of form factors (straight (T5, T8, T12), circular (TL-E) and compact (PL-S/PL-L)) and wattages enables you to make all kinds of designs for your electronic fly killers

Warnings and Safety

- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Product data

General Information		UV Depreciation at 500 h	
Cap-Base	G5 [G5]	17 %	
Life to 50% Failures (Nom)	10,000 hour(s)	UV Depreciation at 8000 h	
Useful Life (Nom)	5,000 hour(s)	60 %	
Light Technical		Operating and Electrical	
Color Code	10	Power Consumption	6 W
Color Designation	Actinic	Lamp Current (Nom)	0.16 A
Chromaticity Coordinate X (Nom)	222	Voltage (Nom)	42 V
Chromaticity Coordinate Y (Nom)	210	Voltage (Nom)	42 V
UV Depreciation at 1000 h	25 %	Mechanical and Housing	
UV Depreciation at 2000 h	35 %	Bulb Shape	T16 [T 16mm]
UV Depreciation at 5000 h	50 %		

Actinic BL TL(-K) / TL-D(-K)

Approval and Application

Mercury (Hg) Content (Nom) 4.4 mg

UV

UV-A Radiation 100Hr (IEC) 1.4 W

Product Data

Full product code 871150026039027

Order product name Actinic BL TL 6W/10 1FM/10X25CC

Order code 928000501030

Numerator - Quantity Per Pack 1

Numerator - Packs per outer box 250


Material Nr. (12NC) 928000501030

Full product name Actinic BL TL 6W/10 1FM/10X25CC

EAN/UPC - Case 8711500260413


EAN/UPC - Product/Case 8711500260390

Dimensional drawing



Product	D (max)	A (max)	B (max)	B (min)	C (max)
Actinic BL TL 6W/10 1FM/10X25CC	16 mm	212.1 mm	219.2 mm	216.8 mm	226.3 mm

Photometric data



Spectral Power Distribution Colour - Actinic BL TL 6W/10 1FM/10X25CC

