

XBO 3000 W/HTP XL OFR

XBO Xtreme Life | Xenon short-arc lamps for cinema projection



Product benefits

- Short arc with very high luminance for brighter screen illumination
- Constant color temperature of 6,000 K throughout the entire lamp lifetime
- Easy to maintain
- High arc stability
- Instant light on screen thanks to hot restart function
- Wide dimming range

Product features

- Wattage: 1,200...8,000 W



October 30, 2016, 19:26:40 XBO 3000 W/HTP XL OFR

Product datasheet

Technical data

Electrical data

Nominal wattage	3000.00 W	
Lamp voltage	29 V	
Nominal current	100 A	
Lamp current	100 A	
Current control range	60110 A	

Dimensions & weight

Diameter	60.0 mm	
Length	405.0 mm	
Length with base excl. base pins/connection	357.00 mm	
Light center length (LCL)	162.5 mm ¹⁾	
Electrode gap cold	6.0 mm	
Cable/wire length, input side	-	
Product weight	591.30 g	

¹⁾ Distance from end of base to tip of electrode (cold)

Temperatures & operating conditions

	Max. permitted ambient temp. pinch point	230 °C
--	--	--------

Lifespan

Lifespan	2200 h

Additional product data

Base anode (standard designation)	SFa27-14
Base cathode (standard designation)	SFc27-14

Product datasheet

Capabilities

Cooling	Forced ¹⁾
Burning position	s30/p30 ²⁾

1) Vertical and horizontal

²⁾ For vertical burning position: anode (+) on top

Country specific information

Product code	METEL code	SEG-No.	STK-Number	UK Org
4008321244017	OSRXBO3000HTPXL	-	-	-

Product datasheet

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4008321244017	XBO 3000 W/HTP XL OFR	Shipping carton box 1	590 mm x 229 mm x 234 mm	31.62 dm ³	1677.30 g
4008321650436	XBO 3000 W/HTP XL OFR	Shipping carton box 1	590 mm x 234 mm x 229 mm	31.62 dm³	1677.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.