

# XBO 6500 W/DHP OFR

XBO DHP for digital cinema projection | Xenon short-arc lamps



## Areas of application

- Cinema projection

### Product family features

- Short arc with highest luminance for brighter screen illumination
- A lifetime of reliable performances with constant 6000 K color temperature
- Easy to maintain
- High level of arc stability
- Hot restart and instant light on screen
- Dimmable in a wide range








## Product datasheet

### Technical data

## **Electrical data**

Nominal current	165 A
Nominal wattage	6500.00 W
Current control range	133173 A
Nominal voltage	39.0 V

## Dimensions & weight



Diameter	78.0 mm
Length	436.0 mm
Length with base excl. base pins/connection	393.00 mm
Cable/wire length, input side	155 mm
Light center length (LCL)	170.5 mm <sup>1)</sup>
Electrode gap cold	7.5 mm
Product weight	1000.00 g
Cable length	155.0 mm

 $<sup>^{1)}</sup>$  Distance from end of base to tip of electrode (cold)

## Temperatures & operating conditions

Max. permitted ambient temp. pinch point	230 °C
--	--------

## Lifespan

Lifespan	500 h
Service Warranty Lifetime	750 h

## Additional product data

Base anode (standard designation)	SFaX30-9.5
Base cathode (standard designation)	SFa30-7.9

# Product datasheet

# Capabilities

Cooling	Forced
Burning position	s15/p15 <sup>1)</sup>

 $<sup>^{1)}</sup>$  For vertical burning position: anode (+) on top

#### Product datasheet

#### Safety advice

Because of their high luminance, UV radiation and internal pressure in both the hot and cold state, XBO lamps may only be operated in enclosed lamp casings specially constructed for the purpose. Xenon lamps are highly explosive. When hot, xenon lamps can cause burn marks. They should only be handled when the lamp is at room temperature. Always use the protective jackets supplied when handling these lamps. When packing the lamps and when installing or removing the lamps without their protective jackets, always wear protective clothing (face shield with neck protector, protective jacket and lint-free, cut-resistant gloves). For more information see the relevant in-pack leaflets and operating instructions.

#### Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4008321676078	XBO 6500 W/DHP OFR	Shipping carton box 1	670 mm x 309 mm x 309 mm	63.97 dm³	3312.60 g
4062172030731	XBO 6500 W/DHP OFR	Shipping carton box	590 mm x 234 mm x 234 mm	32.31 dm³	2149.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

#### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.