OSRAM

Xstage 7000 W OFR

Xstage | Xenon short-arc lamps for entertainment

Areas of application

- Xenon short-arc lamps for event and architecture lighting

Product benefits

- Higher luminance thanks to the shorter arc
- Optimized base for better stability
- Optimized compact design

Product features

- Color temperature: approx. 6,000 K (Daylight)
- Dimmable
- Hot restart capability

Product datasheet

Electrical data

Nominal wattage	7000.00 W
Nominal voltage	40.0 V
Lamp current	160 A
Current control range	110...165 A

Photometrical data

Luminous flux	330000 lm
Luminous intensity	33000 cd

Dimensions & weight

Diameter	70.0 mm
Length	400.0 mm
Mounting length	362.0 mm
Light center length (LCL)	162.5 mm

Lifespan

Lifespan	1000 h

Additional product data

Base anode (standard designation)	SFaX27-9.5
Base cathode (standard designation)	SFc28-27

October 24, 2016, 18:29:06

Xstage 7000 W OFR

Page 2 of 3

Product datasheet

Safety advice

Because of their high luminance, UV radiation and high internal pressure in both the hot and cold state, Xstage lamps must only be operated in enclosed lamp casings specially constructed for the purpose. Always use the supplied protective jackets when handling these lamps. They may only be used as open lamps if appropriate safety measures are taken. More information is available on request or can be found in the leaflet included with the lamp or the operating instructions.

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4008321288851	Xstage 7000 W OFR	Shipping carton box 1	590 mm x 229 mm x 234 mm	31.62 dm³	2058.40 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

—