



# MSR Gold™ MiniFastFit (Touring/ Stage)

## MSR Gold 1000 MiniFastFit 1CT/4

Thanks to the specially designed lamp base, the MSR Gold™ MiniFastFit takes just seconds to replace, to help ensure non-stop clubbing entertainment. In addition, the innovative gold plated pins ensure excellent current transfer to prolong lamp and lamp holder lifetimes and thereby reduce lamp replacement costs. Easy handling and small compact fixture designs are allowed by the lamps compact size, while the very short arc provides a high perceived brightness and high beam intensity.

### Warnings and Safety

- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

### Product data

General Information	
Cap-Base	PGJX36 [PGJX36]
Operating Position	UNIVERSAL [Any or Universal (U)]
Life to 50% Failures (Nom)	900 hour(s)
Light Technical	
Color Code	- [Not Specified]
Luminous Flux	82,000 lumen
Chromaticity Coordinate X (Nom)	0.321
Chromaticity Coordinate Y (Nom)	0.330
Correlated Color Temperature (Nom)	6000 K


Luminous Efficacy (rated) (Nom)	82 lm/W
Color rendering index (CRI)	80
Operating and Electrical	
Power Consumption	1,000.0 W
Lamp Current (Nom)	11.4 A
Controls and Dimming	
Dimmable	Yes

MSR Gold™ MiniFastFit (Touring/Stage)

Product Data	
Full product code	871829178508800
Order product name	MSR Gold 1000 MiniFastFit 1CT/4
Order code	928171405115
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	4

Material Nr. (12NC)	928171405115
Full product name	MSR Gold 1000 MiniFastFit 1CT/4
EAN/UPC - Case	8718291785095
EAN/UPC - Product/Case	8718291785088

Dimensional drawing



Product	D (max)	O	L (min)	L (max)	L	C (max)	F (max)	F	F (min)
MSR Gold 1000 MiniFastFit 1CT/4	26 mm	5.5 mm	55 mm	57 mm	56 mm	112 mm	36.5 mm	36 mm	35.3 mm

