# Product datasheet



# HBO 2510 W/NIL

HBO-IC Microlithography lamps for Nikon i-line systems | Microlithography lamps for Nikon i-line systems





June 20, 2021, 09:47:32 HBO 2510 W/NIL


# Product datasheet

### Technical data

### **Electrical data**

Nominal voltage	23.0 V
Nominal current	109 A
Type of current	DC
Rated wattage	2500.00 W
Nominal wattage	2500.00 W

## Dimensions & weight



Diameter	70.0 mm	
Length	357.0 mm	
Length with base excl. base pins/connection	325.00 mm	
Light center length (LCL)	157.75 mm <sup>1)</sup>	
Electrode gap cold	4.5 mm	

 $^{1)}$  Distance from end of base to tip of anode or cathode (cold)

### Additional product data

Base anode (standard designation)	SFc33.5-12/50 <sup>1)</sup>
Base cathode (standard designation)	SFc33.5-14/50

 $^{1)}$  With cable connection (M 8)

## Capabilities

Cooling	Forced <sup>1)</sup>
Burning position	Other <sup>2)</sup>

1) Maximum permissible base temperature: 200 °C  $\,$ 

<sup>2)</sup> Anode on top

## Product datasheet

#### Safety advice

Because of their high luminance, UV radiation and high internal pressure (when hot) HBO lamps may only be operated in enclosed lamp casings specially constructed for the purpose. Mercury is released if the lamp breaks. Special safety precautions must be taken. More information is available on request or can be found in the leaflet included with the lamp or in the operating instructions.

#### Logistical Data

Dimensions (length x width x height) 605 mm x 320 mm x	<b>Volume</b> 44.53 dm <sup>3</sup>	Gross weight
	44 53 dm <sup>3</sup>	
230 mm		3401.00 g
- x - x -		
800 mm x 600 mm x 825 mm	396.00 dm <sup>3</sup>	21782.00 g
- x - x -		
795 mm x 820 mm x 598 mm	389.84 dm³	9500.00 g
795 mm x 820 mm x 598 mm	389.84 dm³	14000.00 g
2 2 7 2 7	800 mm x 600 mm x 825 mm - x - x - 795 mm x 820 mm x 598 mm 795 mm x 820 mm x	800 mm x 600 mm x 396.00 dm <sup>3</sup> 825 mm - x - x - 795 mm x 820 mm x 389.84 dm <sup>3</sup> 598 mm 795 mm x 820 mm x 389.84 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

#### References / Links

For further information on HBO lamps and notes for manufacturers of control gear, please refer to the following publications, available on request from OSRAM:

"Specifications for power supply units for dc operated HBO mercury short-arc lamps"

"Specifications for power supply units for ac operated HBO mercury short-arc lamps"

"Specifications for igniters for HBO mercury short-arc lamps"

"Availability of power supplies and igniters"

"Mercury short arc lamps HBO for microlithography, Technology and Application"

#### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.