



# CorePro LED PLC 2P



## CorePro LED PLC 6.5W 840 2P G24d-2

CorePro LED PLC 2P integrates a LED light source into a traditional fluorescent form factor. This product is the ideal solution for uplampping in general lighting applications: it meets basic lighting requirements, offers significant energy savings, and is environmentally friendly.

### Product data

General Information	
Cap-Base	G24D-2 [G24d-2]
Nominal lifetime	30,000 hour(s)
Switching Cycle	50,000
Lighting Technology	LED
Flux measurement reference	Sphere
CE mark	Yes
EU RoHS compliant	Yes

Light Technical	
Color Code	840 [CCT of 4000K]
Beam Angle (Nom)	120 degree(s)
Luminous Flux	700 lumen
Color Designation	Cool White (CW)
Correlated Color Temperature (Nom)	4000 K
Luminous Efficacy (rated) (Nom)	92.31 lm/W
Color Consistency	<6
Color rendering index (CRI)	83
LLMF At End Of Nominal Lifetime (Nom)	70 %
Photobiological safety according to EN 62471 RGO	

Operating and Electrical	
Line Frequency	50 to 60 Hz

Input Frequency	50 to 60 Hz
Power Consumption	6.5 W
Starting Time (Nom)	0.5 s
Warm-up time to 60% light	0.5 s
Power Factor (Fraction)	0.9
Voltage (Nom)	220-240 V
LED alternative to fluorescent lamp power	18 W

Temperature	
Ambient temperature range	-20 °C to 35 °C
T-Case Maximum (Nom)	65 °C

Controls and Dimming	
Dimmable	No

Mechanical and Housing	
Bulb Material	Plastic
Product Length	100 mm
Bulb Shape	Tube, single-ended

Approval and Application	
Energy Efficiency Class	F
Energy Saving Product	Yes

CorePro LED PLC 2P

Approval Marks	TUV CE marking RoHS compliance KEMA Keur certificate
Energy Consumption kWh/1000 h	7 kWh
EPREL Registration Number	403557
Product Data	
Full product code	871869654129600
Order product name	CorePro LED PLC 6.5W 840 2P G24d-2
Order code	929001201502


Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	10
Material Nr. (12NC)	929001201502
Full product name	CorePro LED PLC 6.5W 840 2P G24d-2
EAN/UPC - Case	8718696541302
EAN/UPC - Product/Case	8718696541296

Dimensional drawing




Product	D1	D2	A1	A2	A3
CorePro LED PLC 6.5W 840 2P G24d-2	24.3 mm	28.4 mm	105.8 mm	125 mm	147.6 mm


Photometric data



General uniform lighting - CorePro LED PLC 6.5W 840 2P G24d-2





Spectral Power Distribution Colour - CorePro LED PLC 6.5W 840 2P G24d-2




Light Distribution Diagram - CorePro LED PLC 6.5W 840 2P G24d-2

CorePro LED PLC 2P


Lifetime




Life Expectancy Diagram - CorePro LED PLC 6.5W 840 2P G24d-2



Life Expectancy Diagram - CorePro LED PLC 6.5W 840 2P G24d-2



Life Expectancy Diagram - CorePro LED PLC 6.5W 840 2P G24d-2



Lumen Maintenance Diagram - CorePro LED PLC 6.5W 840 2P G24d-2

Lumen Maintenance Diagram - CorePro LED PLC 6.5W 840 2P G24d-2

## CorePro LED PLC 2P

