



# Halogen FastFit

## 7019G 750W 115V FastFit

Halogen FastFit lamps are replaced in seconds - thanks to the specially designed base. The compact filament ensures high beam intensity, while the shock-resistant design allows easy handling and reliable use in moving head systems. In addition, the highly innovative P3 technology allows use at higher temperatures, which further extends lifetime and consistency of light output. P3 technology also allows the lamp to be used in any burning position and enables more compact designs of fixtures. And because the FastFit design is also applied to Philips MSR/MSD Gold™ lamps, switching lamp technologies is also quick and easy.

### Product data

General Information	
Cap-Base	PGJX50 [ PGJX50]
Philips Code	7019G
ANSI Code	GRS
Operating Position	UNIVERSAL [ Any or Universal (U)]
Main Application	Entertainment
Life To 50% Failures (Nom)	300 h
System Description	P3 Technology

Light Technical	
Luminous Flux (Rated) (Nom)	20500 lm
Correlated Color Temperature (Nom)	3200 K

Operating and Electrical	
Power (Rated) (Nom)	750 W
Rapid Acting HBC Fuse	10 V
Voltage (Nom)	115 V

Controls and Dimming	
Dimmable	Yes

Mechanical and Housing	
Bulb Finish	Clear
Filament Shape	Bi-Plane
Filament Dimensions WxH	9,5 x 9

Luminaire Design Requirements	
Pinch Temperature (Max)	500 °C


  

Product Data	
Full product code	872790080739400
Order product name	7019G 750W 115V FastFit
EAN/UPC - Product	8727900807394
Order code	924582434428
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	10

# Halogen FastFit

Material Nr. (12NC)	924582434428
Net Weight (Piece)	0.130 kg

## Dimensional drawing



7019G 750W 115V FastFit

Product	D	H	W	L	C	E
7019G 750W 115V FastFit	19 mm	9 mm	9.5 mm	79 mm	140 mm	41 mm

