

2352MFX6

ORIGINAL | Lamps for printed circuit boards



Areas of application

- Instrument and switch lighting

Product benefits

- OEM Quality
- Wide product range
- Reliable quality

Product features

- Original spare parts

Technical data


Electrical data

Power input	2.13 W
Nominal voltage	12.0 V
Nominal wattage	2.00 W
Power input tolerance	±10 %
Test voltage	13.5 V

Photometrical data

Luminous flux	11.8 lm
Luminous flux tolerance	±20 %

Dimensions & weight



Length	17.5 mm
Diameter	5 mm
Product weight	0.74 g

Colors & materials

Base color	Pale green
------------	------------

Lifespan

Lifespan B3	1500 h
Lifespan Tc	6000 h

Additional product data

Base (standard designation)	BX8.4d
-----------------------------	--------

Capabilities

Product datasheet

Thickness of PCB	1.25 mm
------------------	---------

Certificates & standards

ECE category	-
Approval marks – approval	-

Country specific categorizations

Order reference	2352MFX6
-----------------	----------

Country specific information

Product code	METEL code	SEG-No.	STK-Number	UK Org
4008321097149	OSRA2352MFX6	-	-	-

Product datasheet

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4008321097149	2352MFX6	Unpacked 1	17 mm x 12 mm x 12 mm	0.00 dm ³	1.00 g
4008321097156	2352MFX6	Folding carton box 10	46 mm x 29 mm x 112 mm	0.15 dm ³	18.29 g
4008321097163	2352MFX6	Shipping carton box 50	148 mm x 115 mm x 55 mm	0.94 dm ³	121.39 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.