



# CorePro LEDlinear MV



## CorePro LED linear D 14-120W R7S 118 830

CorePro R7S is a retrofit replacement for traditional double-ended linear R7S lamps. Its 'light all around' design delivers light just like a halogen lamp. Within the range you can choose dimmable products which have deep dimming function that enables a cozy ambience when using a dimmable fixture.

### Product data

General Information		Power Consumption	
Cap-Base	R7S [R7s]	Lamp Current (Nom)	14 W
Nominal lifetime	15,000 hour(s)	Wattage Equivalent	75 mA
Switching Cycle	50,000	Starting Time (Nom)	120 W
Lighting Technology	LED	Warm-up time to 60% light	0.5 s
CE mark	Yes	Power Factor (Fraction)	0.5 s
EU RoHS compliant	Yes	Voltage (Nom)	0.8
Light Technical		Temperature	
Color Code	830 [CCT of 3000K]	T-Case Maximum (Nom)	220-240 V
Luminous Flux	2,000 lumen	Controls and Dimming	
Color Designation	White (WH)	Dimmable	Yes
Correlated Color Temperature (Nom)	3000 K	Mechanical and Housing	
Luminous Efficacy (rated) (Nom)	142.86 lm/W	Bulb Shape	Linear
Color Consistency	<6	Approval and Application	
Color rendering index (CRI)	80	Energy Efficiency Class	D
LLMF At End Of Nominal Lifetime (Nom)	70 %	Energy Consumption kWh/1000 h	14 kWh
Flickering value (PstLM)	1	EPREL Registration Number	397582
Stroboscopic effect value (SVM)	0.4	EyeComfort	Yes
Operating and Electrical			
Line Frequency	50 to 60 Hz		
Input Frequency	50 to 60 Hz		

CorePro LEDlinear MV


Product Data	
Full product code	871869671400300
Order product name	CorePro LED linear D 14-120W R7S 118 830
Order code	929001353602
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	10

Material Nr. (12NC)	929001353602
Full product name	CorePro LED linear D 14-120W R7S 118 830
EAN/UPC - Case	8718696714010
EAN/UPC - Product/Case	8718696714003


Dimensional drawing

Product	D	C
CorePro LED linear D 14-120W R7S 118 830	29 mm	118 mm


Photometric data



General uniform lighting - CorePro LED linear D 14-120W R7S 118 830



Spectral Power Distribution Colour - CorePro LED linear D 14-120W R7S 118 830



Light Distribution Diagram - CorePro LED linear D 14-120W R7S 118 830

Lifetime



Life Expectancy Diagram - CorePro LED linear D 14-120W R7S 118 830



Lumen Maintenance Diagram - CorePro LED linear D 14-120W R7S 118 830

