



CorePro LEDlinear MV

CorePro LEDlinear ND 7.5-60W R7S 78mm830

CorePro R7S is a retrofit replacement for traditional double-ended linear R7S lamps. Its 'light all around' design delivers light just like a halogen lamp. The deep dimming function enables a cozy ambience when using a dimmable fixture.


Product data

General Information		Warm Up Time To 60% Light (Nom)		0.5 s
Cap-Base	R7S [R7s]	Power Factor (Nom)		0.5
Nominal Lifetime (Nom)	15000 h	Voltage (Nom)		220-240 V
Switching Cycle	50000X			
Technical Type	7.5-60W			
		Temperature		
		T-Case Maximum (Nom)		104 °C
		Controls and Dimming		
		Dimmable		No
		Approval and Application		
		Energy Efficiency Label (EEL)		A++
		Energy Consumption kWh/1000 h		8 kWh
		Product Data		
		Full product code		871869671394500
		Order product name		CorePro LEDlinear ND 7.5-60W R7S 78mm830
		EAN/UPC - Product		8718696713945
		Order code		929001339002
		Numerator - Quantity Per Pack		1
		Numerator - Packs per outer box		10
		Material Nr. (12NC)		929001339002
		Net Weight (Piece)		0.045 kg

Light Technical	
Color Code	830 [CCT of 3000K]
Luminous Flux (Nom)	950 lm
Luminous Flux (Rated) (Nom)	950 lm
Color Designation	White (WH)
Correlated Color Temperature (Nom)	3000 K
Luminous Efficacy (rated) (Nom)	126.67 lm/W
Color Consistency	<6
Color Rendering Index (Nom)	80
LLMF At End Of Nominal Lifetime (Nom)	70 %

Operating and Electrical	
Input Frequency	50 to 60 Hz
Power (Rated) (Nom)	7.5 W
Lamp Current (Nom)	70 mA
Wattage Equivalent	60 W
Starting Time (Nom)	0.5 s




Dimensional drawing



Linear 220V 8-60W 806lm 3000K R7S ND


Product	D	C
CorePro LEDlinear ND 7.5-60W R7S 78mm830	29 mm	78 mm

Photometric data




CorePro LEDlinear MV 60W R7S 830 Linear

Lifetime



LEDbulb 60W E14 827 FR B38



LEDbulb 60W E14 827 FR B38

