



HALOGENLAMPEN mit Stiftsockel G4; G6,35; GY6,35

HALOGEN LAMPS with bi-pin cap G4, G6.35, GY6.35



Halogenlampen mit Stiftsockel gibt es als Kombinationen aus unterschiedlichsten Leuchtkörpern und Sockelformen. In vielen Anwendungen eingesetzt sind sie relativ klein und lassen sich leicht austauschen. Die parallelen Stifte aus Molybdän (Pins) bleiben auch bei höheren Temperaturen kontaktsicher und oxidationsfrei. Jeder Stift ist am freistehenden Ende abgerundet, um das Einstecken der Lampen in der Fassung zu erleichtern.

Hauptmerkmale:

- Diverse Leuchtkörperformen
- Gute Farbwiedergabe und hohe Farbtemperatur
- Leichte Installation und Austauschbarkeit
- Quarzglas ohne UV-reduzierende Eigenschaften

Anwendungsbereiche:

Mikroskopie, Projektion, Analyse, Operations- und Dentalleuchten


Halogen lamps with bi-pin caps are available with varying combinations of filaments and cap shapes. Used in a variety of applications, they are relatively small and can be easily replaced. The parallel pins made from molybdenum remain securely connected and free from oxidation, even at high temperatures. The exposed end of each pin is rounded so that the lamp plugs easily into the lamp socket.

Main features:


- Various filament shapes
- Good colour rendering and a high colour temperature
- Simple to install and replace
- Quartz glass without UV-reducing properties

Fields of application:

Microscopy, projection, analysis, surgical and dental lights



1



2



Artikel Reference	Typ Type	Spannung Voltage V	Leistung Wattage W	Sockel Cap	Lichtstrom Lumens Lm	Lebensdauer Life h	Leuchtkörper Filament	Abmessungen Dimension b x h mm	
55911	HLWS4	6	10	G4	195	100	C-6	1,9 x 0,5	①
55119	HLL	6	10	G4	150	2000	C-6	3,0 x 0,5	①
55909	HLL	6	10	G4	205	100	C-6	2,0 x 1,0	①
55912	HLL	6	20	G4	300	1000	CBAR-6	2,0 x 2,0	①
55913	HLWS4	6	20	G4	450	100	CBAR-6	1,9 x 1,4	①
55126	HLL	6	20	G4	475	100	C-6	1,6 x 0,6	①
55146	HLWS	6	25	G4	510	100	CBAR-6	1,7 x 1,7	①
55165	HLL	6	30	G4	765	100	CBAR-6	1,5 x 1,5	①
55917	HLL	12	20	G4	300	2000	C-6	3,5 x 0,85	①
55919	HLL	12	20	G4	350	1000	CBAR-6	1,9 x 1,9	①
55906	HLL	12	20	G4	350	2000	C-6	3,5 x 0,85	①
55136	HLL	12	20	G4	350	2000	C-6	2,8 x 1,0	①
55137	HLL	12	20	G4	640	100	C-6	3,0 x 0,8	①
55928	HLL	12	50	G6,35	1000	2000	CBAR-6	3,5 x 2,4	②
55921	HLWS4	12	50	G6,35	1400	50	CBAR-6	3,3 x 1,6	②