

SHP Standard

SHP-70W/CO/I V2 E27 SLV

0020694



Product features

• - A high pressure soldium lamp with internal ignitor, - Cost reduction opportunities since no ignitor or external wiring is required, - Enables lumiaire size to be reduced since no ignitor is required, - Available in a coated eliptical bulb, - Popular choice for parks, gardens, pedestrian zones and residential streetlighting, - Also for use as low-cost illumination of workshops and small industrial areas













PRODUCT OVERVIEW

Product code	0020694
Product name	SHP-70W/CO/I V2 E27 SLV
Technology	HID
Watt (Rated) (W)	70
Fixture rating	Enclosed
General application	Logistics & Industry,
Certifications	EUTIE064
ETIM Class	EC000821
Luminous flux (lm)	5800
Colour temperature (K)	2050
Light colour	N/A
CRI (Ra)	20
Wattage (W)	70
Product Voltage (V)	90
Dimmable	No
Average life (Nominal) (h)	20000
Product EAN number	5410288206943

DATA TABLE

0020694
SHP-70W/CO/I V2 E27 SLV
HID
70
Enclosed
Logistics & Industry,
EUTIE064
EC000821



SHP Standard

SHP-70W/CO/I V2 E27 SLV

0020694

Optical data

Luminous flux (lm)	5800
Luminous flux (Rated) (lm)	5800
Efficacy (Rated) (lm/w)	83
Ambient temperature for maximum luminous flux (°C)	25
Colour temperature (K)	2050
Light colour	N/A
CRI (Ra)	20
Rated lumen maint. factor (%) at 2000 h 50Hz	98
Rated lumen maint. factor (%) at 4000 h 50Hz	96
Rated lumen maint. factor (%) at 6000 h 50Hz	94
Rated lumen maint. factor (%) at 8000 h 50Hz	93
Rated lumen maint. factor (%) at 12000 h 50Hz	91
Rated lumen maint. factor (%) at 16000 h 50Hz	90
Rated lumen maint. factor (%) at 20000 h 50Hz	89

Electrical data

Wattage (W)	70
Current (A)	0.98
Mains voltage (V)	220-240V~
Product Voltage (V)	90
Control gear required	Yes
Transformer required	No
Dimmable	No
Lamp Energy Label (class)	A
kWh per 1000 hours burning time	77

Lifetime data

Average life (Nominal) (h)	20000
Average life (Rated) (h)	20000
Rated survival factor (%) at 2000 h 50Hz	99
Rated survival factor (%) at 4000 h 50Hz	96
Rated survival factor (%) at 6000 h 50Hz	92
Rated survival factor (%) at 8000 h 50Hz	87
Rated survival factor (%) at 12000 h 50Hz	76



SHP Standard

SHP-70W/CO/I V2 E27 SLV

0020694

Rated survival factor (%) at 16000 h 50Hz	63
Rated survival factor (%) at 20000 h 50Hz	50
Physical data	
Max. Lamp Diameter (mm) - D	72
Weight (kg)	0.059
Packaging	
Single packaging type	Carton
Product EAN number	5410288206943
Packaging single length (cm)	7.0
Packaging single width (cm)	7.0
Packaging single height (cm)	16.5
DUN14 (outer)	15410288206940
Units per outer package	24
Packaging outer length (cm)	45.5
Packaging outer width (cm)	30.5
Packaging outer height (cm)	18.5
Safety data	
Lamp mercury content (mg)	10.8
Breakage cleaning instructions	applicable
Recommendation for disposal at end of life	Applicable
Special purpose lamp	No
Suitable for household illumination	No
Safety message	Not Suitable for totally enclosed fixtures



SHP Standard SHP-70W/CO/I V2 E27 SLV **0020694**

