

**Logistic Data**

Article No.	31110327
Code	NL-T5 8W/640/G5
Product EAN	4008597103278
Customs tariff no.	85393110
Box quantity (pcs.)	25
EAN Box	4008597403279
Gross weight of box in kg	0.96
Length of box in m	0.33
Width of box in m	0.11
Height of box in m	0.11
ETIM class	EC000108
ETIM class name	Fluorescent lamp
Product status	Active

**Electric Parameters**

Lamp nominal wattage	8 W
Rated wattage	8.0 W
Energy Consumption kWh/1000h	8.8
Mains voltage	230 V



**Light Application Parameters**

Luminous flux	385 lm
Luminous flux	385 lm
max. luminous flux at	25 °C
Luminous efficiency	48.13 lm/W
Radium light colour	Bright white
Colour temperature	4300 K
Colour rendering index Ra	60-69
Mean luminance	0.95

**Service Life**

Mean service life	10000 h
-------------------	---------





## Specification

Length max.	288 mm
dimable	ja
Lamp shape	Rod

## Notes

Please, refer to [www.radium.de/recycling](http://www.radium.de/recycling) for notes on disposal of burned-out lamps as well as lamp breakage.

The field 'info about service life' contains the frame conditions according to standards based on which the specific service life has been determined. So, for example, "12B50, 50Hz" means that the mean service life (B50) has been determined with a 12h switching cycle at mains (frequency 50Hz), "3B50, HF" is based on a 3h switching cycle at electronic control gear (high frequency).

**Notes**

**Base**





G5  
IEC/EN 60061-1  
sheet 7004-52-5

**Spectrum**

Natural daylight is a mixture of direct sunlight and the light of the sky. Therefore, its spectral composition changes permanently due to the changing time of day. The standardised light classification D65 corresponds to a daylight with a colour temperature of approximately 6500 K.

Every fluorescent lamp type has got an individual spectral power distribution according to its phosphor coating inside the bulb. From this result important properties light colour or colour rendering.

Visible region from 380 to 780 nm; height of graph corresponding with relative spectral emission (400mW/klm) per 10nm.



daylight(D 65)

**Special features**



**General notes**

The technical design data in accordance with DIN and IEC. The producer does not take any responsibility for damage to persons or property in case of unsuitable operation or handling of the product. Operating data and dimensions are valid within the usual tolerances. Related lamp types (different bases, mains voltages) may be available on request. Sale and delivery are effected in accordance with the Radium Terms of Delivery and Payment valid on the day of conclusion of contract. Packing units offer economical advantages to the purchase and logistic department. Please match your quantity volume accordingly. For orders of a minimum quantity (clefts) with a lamp model the amount lower than the volume of each packaging unit, we will invoice 10 % additional charge per lamp type. Technical changes and terms of delivery are reserved. Manipulation of any kind to packaging or product is not permissible as this will violate Radium brand rights. Furthermore, technical properties of the product can change to its disadvantage or even destruction. Therefore, Radium cannot be responsible for consequential damages.

® = Registered trademark

Subject to change without notice. Errors and omissions excepted.

**All technical data without guarantee.**