



Capsules LV 3000 h

Caps 3000h 14W GY6.35 12V CL 1CT/10x10F

Low-voltage halogen capsule. Ideal solution for small decorative luminaires. UV-block glass and low-pressure filling allow usage without cover glass. The compact halogen capsule delivers crisp white light over a long lifetime.


Product data

| General Information | |
|------------------------------------|-----------------------------------|
| Cap-Base | GY6.35 [GY6.35] |
| Operating Position | UNIVERSAL [Any or Universal (U)] |
| Nominal Lifetime (Nom) | 3000 h |
| Switching Cycle | 12000X |
| Light Technical | |
| Luminous Flux (Nom) | 232 lm |
| Luminous Flux (Rated) (Nom) | 232 lm |
| Correlated Color Temperature (Nom) | 2900 K |
| Luminous Efficacy (rated) (Nom) | 16.6 lm/W |
| Color Rendering Index (Nom) | 100 |
| Operating and Electrical | |
| Power (Rated) (Nom) | 14.0 W |
| Lamp Current (Nom) | 1.167 A |
| Starting Time (Nom) | 0.0 s |
| Warm Up Time to 60% Light (Nom) | instant full light s |
| Power Factor (Nom) | 1 |
| Voltage (Nom) | 12 V |
| Controls and Dimming | |
| Dimmable | Yes |

| Mechanical and Housing | |
|---------------------------------|---|
| Bulb Finish | Clear |
| Approval and Application | |
| Energy Efficiency Label (EEL) | B |
| Energy Consumption kWh/1000 h | 14 kWh |
| Luminaire Design Requirements | |
| Bulb Temperature (Max) | 600 °C |
| Pinch Temperature (Max) | 350 °C |
| Product Data | |
| Full product code | 871869682777200 |
| Order product name | Caps 3000h 14W GY6.35 12V CL 1CT/10x10F |
| EAN/UPC - Product | 8718696827772 |
| Order code | 925723517101 |
| Numerator - Quantity Per Pack | 1 |
| Numerator - Packs per outer box | 100 |
| Material Nr. (12NC) | 925723517101 |
| Net Weight (Piece) | 0.003 kg |

Capsules LV 3000 h

Dimensional drawing



EcoHalo Capsule Gy6.35 12v14w CL B3000

| Product | D (max) | L | C (max) |
|---|---------|-------|---------|
| Caps 3000h 14W GY6.35 12V CL 1CT/10x10F | 12 mm | 30 mm | 44 mm |

